	024 EDWA		; NE			; Sec 1/4 ; 20						
1 1/2 W.		TROUSDALE,	KS		·	address of we			•	-		
		Box # : F			243		Board o	f Agricul	ture, Div	vision of	Water Resour	rces
lity, St	ate, ZIP	code : l	LEWIS, K	S 67	552- 		Applica	tion Numbe				
	ELL'S LOC N SECTION					ETED WELL <b>7</b> ( iwater Encounte			ft. 2	2.	ft. 3.	f
\	: : : :	: ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	ŧ	1		TER LEVEL 2: estdata: Well						g
	i i i		1 ;	•	mated Yield	gpm: Well	water was	ft	after	hou	rs pumping	g
			<u>:</u>	E ¦ Bore	Hole Diamete	er <b>8.</b> 75	in. to	<b>70</b> ft., a	ınd	in. to	ft.	
!	SH	: SE		WELL	WATER TO BE	USED AS: 01 DO	MESTIC					
, ! , !	! :	1 1	! !	; If y		acteriological r sample was su						ted? \
Blank ca Casing h TYPE OF	neight abo SCREEN DR		rface ON MATER	12 in., IAL: <b>07</b>	weight <b>PVC</b>	in. to lbs/ft.	₩all thic	kness or (	gauge No.	26		
Plank ca Casing h TYPE OF GCREEN O	neight abo SCREEN OR DR PERFORA	ve land sur PERFORATIO	rface ON MATER NGS ARE:	12 in., IAL: 07 08 From	weight PVC SAW CUT	1bs/ft. 70 ft., Fro	Wall thic	kness or (	gauge No.	26		
Casing h TYPE OF GCREEN O  GCREEN P	eight abo SCREEN OR OR PERFORA  PERFORATED	ve land sur PERFORATION OPENIA	rface ON MATER NGS ARE: 	12 in., IAL: 07 08 From	weight PVC SAN CUT	1bs/ft. 70 ft., Fro	Wall thic	kness or (  to to to	gauge No.	26		
Olank ca Casing h FYPE OF GCREEN O GCREEN P GROUT MA GROUT MA GROUT In	neight abo SCREEN OR OR PERFORA PERFORATED RAVEL PACK OTERIAL STERIAL STERIAL STERIAL STERIAL STERIAL STERIAL STERIAL STERIAL	PERFORATION OPENING INTERVALS:  ON BENTON OF THE PROPERTY OF T	rface ON MATER NGS ARE: : : ITE ft. to	12 in., IAL: 07 08 From From From	weight PVC SAN CUT  60 ft. to     ft. to     25 ft. to     ft. to	70 ft., Fro ft., Fro 70 ft., Fro	Wall thic	. to . to . to . to	ft. ft.	ft.		
llank ca lasing h YPE OF CREEN O CREEN P GROUT MA FROUT In lhat is	PERFORATED  RAVEL PACK  STERIAL	PERFORATION OPENING INTERVALS:  ON BENTON OF THE PROPERTY OF T	rface ON MATER NGS ARE: :  ITE ft. to of possi	12 in., IAL: 07 08 From From From From brom From From From	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft. ft. ft.	ft.	How many feet	 t?
llank ca lasing h YPE OF CREEN O GREEN P GROUT MA FROUT In What is	PERFORATED  RAVEL PACK  PERFORATED  RAVEL PACK  PERFORATED  TERIAL  the neare  on from we  TO  12	PERFORATION OPENING INTERVALS:  ON BENTON: From St source (11? ALL	rface ON MATER NGS ARE: : : ITE ft. to of possi	12 in., IAL: 07 08 From From From	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft. ft. ft.	ft.		 t?
lank ca asing h YPE OF CREEN O CREEN P GR GROUT MA FROUT In that is irectio	PEIGHT ABOUT SCREEN OR PERFORATED PACK PACK PACK PACK PACK PACK PACK PACK	PERFORATION OPENING INTERVALS:  OS BENTON: From St source (11? ALL SILT & SILT	rface ON MATER NGS ARE: : : ITE ft. to of possi SAND LAY Y	12 in., IAL: 07 08 From From From From LITHOLOG	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft. ft. ft.	ft.	How many feet	t?
lank ca asing h YPE OF CREEN O CREEN P GR GRUT MA FROUT In that is irectio	PERFORATED  RAVEL PACK  PATERIAL  Itervals:  the neare  TO  12  21	PERFORATION OPENING INTERVALS:  OS BENTON: From St source (11? ALL SILT & SILT	rface ON MATER NGS ARE: :  ITE ft. to of possi SAND LAY	12 in., IAL: 07 08 From From From From LITHOLOG	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft. ft. ft.	ft.	How many feet	
Casing h FYPE OF SCREEN O GREEN P GROUT MA Grout In What is Directio FROM : 12 : 21 :	PEIGHT ABOUT SCREEN OR PERFORATED PACK PACK PACK PACK PACK PACK PACK PACK	PERFORATION OPENING INTERVALS:  OS BENTON: From St source (11? ALL SILT & SILT	rface ON MATER NGS ARE: : : ITE ft. to of possi SAND LAY Y	12 in., IAL: 07 08 From From From From LITHOLOG	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft. ft. ft.	ft.	How many feet	 t?
Casing h FYPE OF SCREEN O GREEN P GROUT MA Grout In What is Directio FROM : 12 : 21 :	PEIGHT ABOUT SCREEN OR PERFORATED PACK PACK PACK PACK PACK PACK PACK PACK	PERFORATION OPENING INTERVALS:  OS BENTON: From St source (11? ALL SILT & SILT	rface ON MATER NGS ARE: : : ITE ft. to of possi SAND LAY Y	12 in., IAL: 07 08 From From From From LITHOLOG	weight PVC SAN CUT  60 ft. to ft. to 25 ft. to ft. to	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft. ft. ft.	ft.	How many feet	
lank ca asing h YPE OF CREEN O 	meight abo SCREEN OR PERFORATED RAVEL PACK STERIAL STE	PERFORATION OPENING INTERVALS:  OS BENTON: From St source (11? ALL BROWN CI) TAN CLAY (05 SAND)	rface ON MATER NGS ARE: : : ITE ft. to of possi  SAND LAY Y AND 17	12 in., IAL: 07 08 From From From From LITHOLOG	weight PVC SAW CUT  60 ft. to ft. to 25 ft. to ft. to  t., From amination: CA	70 ft., Fro ft., Fro 70 ft., Fro ft., Fro ft. to ATTLE PASTURE	Wall thic	to to to TO	ft. ft. ft. ft. ft.	ft.	How many feet	
lank ca asing h YPE OF CREEN O CREEN P  GR ROUT MA rout In hat is irectio FROM : 12 : 33 ;	reight abo SCREEN OR OR PERFORA PERFORATED PERFORATED PACK PACK PACK PACK PACK PACK PACK PACK	PERFORATION OPENING TION OPENING THE PERFORATION OPENING THE PERFORMANCE OF THE PERFORMAN	rface ON MATER NGS ARE: :  ITE ft. to of possi  SAND LAY Y AND 17	12 in., IAL: 07  08  From From From From From LITHOLOG	weight PVC SAW CUT  60 ft. to ft. to 25 ft. to ft. to  1., From amination: CA	70 ft., Fro ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic  om ft  om ft  ft., F  FROM	to to to TO :	ft. ft. ft. ft. sdiction	ft. PLUGGING	How many feet	