

CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4 1/4) Section-Township-Range changed:

listed as SE, SW, SE, sec. 2, T16S, R2W

changed to SE, SW, SE, sec. 2, T25S, R16W

Other changes made:

Initial statements: _____

Changed to: _____

verification method: written description on form, & Belpre 1:24,000 topo. map. initials: ARD date: 12/18/98

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction : Section Number : Township Number : Range Number
 COUNTY: 024 EDWARDS : SE SW 1/4 SE 1/4 1/4 : 2 : T 16 S : R 2 W

Distance and direction from nearest town or city street address of well if located within city?
 4 S. 2 1/2 E. OF BELPRE, KS

2 WATER WELL OWNER: MILDRED SMITH 421 Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: RT.1 BOX 111A
 City, State, ZIP code : MACKSVILLE, KS 67557- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 80 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 0 ft. 3. 0 ft.
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm;
 Estimated Yield 0 gpm; Well water was 0 ft. after 0 hours pumping 0 gpm;
 Bore Hole Diameter 8.75 in. to 80 ft., and in. to 0 ft.
 WELL WATER TO BE USED AS: 01 DOMESTIC
 Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: 02 PVC CASING JOINTS: GLUED
 Blank casing diameter 5 in. to 70 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 0 lbs/ft. Wall thickness or gauge No. 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC
 SCREEN OR PERFORATION OPENINGS ARE: 08 SAW CUT
 SCREEN PERFORATED INTERVALS: From 70 ft. to 80 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 80 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL 03 BENTONITE
 Grout Intervals: From 0 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: CATTLE PASTURE
 Direction from well? ALL How many feet? 6

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|-----------------------|------|----|--------------------|
| 0 | 3 | SILT & SAND | | | |
| 3 | 11 | BROWN CLAY | | | |
| 11 | 17 | GREY CLAY | | | |
| 17 | 26 | 05 SAND AND 17 GRAVEL | | | |
| 26 | 54 | TAN CLAY | | | |
| 54 | 57 | 05 SAND AND 17 GRAVEL | | | |
| 57 | 62 | TAN CLAY | | | |
| 62 | 80 | 05 SAND AND 17 GRAVEL | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 8 /6 /98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 08/22/98 under the business name of CARL HAYSE WATER WELL SVC by (signature) *Carl Hayse*