WATER WEL	I DECODD	Form W	WC.5	Div	ision of Wate	r Resources App. No	20843		
	OF WATER WELL:	Fraction	WC-5		n Number	Township No.	Range Nun	nber	
County: Edward			1/4 NW 1/4		32	T 25 S]E ☑ W	
Street/Rural A	ddress of Well Location;	Global Positioning System (GPS) information:							
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)				
1 1/2 North, 2 3/4 East of Centerview				Longitude: (in decimal degrees)					
1 1/2 North, 2 3/4 East of Contorvior					Elevation:				
2 WATER WELL OWNER					Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Jan Mayhew				Collection Method:					
RR#, Street Address, Box #: 1949 Schultz Aveue				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
City, State, ZIP Code : Haviland, Ks. 67059					Est. Accuracy:				
3 LOCATE WELL									
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 149 tt.									
SECTION BOX	ON BOX: Depth(s) Groundwater Encountered (1)								
N WELL'S STATIC WATER LEVEL. 38									
Pump test data: Well water was .75									
EST. YIELD. 11.53gpm. Well water was .79								gpm	
W F Bore Hole Diameter 35									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
Domestic									
SWSE									
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted									
S 1 mile									
water wen disinfected. Let 100									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .16									
Casing height above land surface. 18 in., Weight Sch 40 lbs./ft., Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)									
The state of the s									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Lowered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN DEDEOR ATED INTERVALS: From 146 ft to 96 ft. Fromtt. to									
From									
GRAVEL PACK INTERVALS: From									
From ft. to ft., From tt. to tt. to ft.									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From ft. to ft., From 20 ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination: Sention tank									
Service large Service Service Service Abandoned water well									
Watertio	ht sewer lines		Fertilizer s	storage	Oil well/g	as well Non	e		
	n well				ell				
FROM TO	LITHOLO		FROM	TO		.OG (cont.) <u>or</u> PLU	J GGING IN	TERVALS	
0 2	Sandy top soil		116	120		clay & sand			
2 4	Sandy brown clay		120	122	Cemented				
4 17	Fine sand		122	125	Small san	d & gravel			
17 23	Sandy tan clay & sand	1	125	133.5	Tan & wh				
23 35	Sand & gravel- clean,		133.5	142		d & gravel			
35 37	Sandy tan clay		142	145		avel mixed			
37 69.5	Sand & gravel- med, of	clean, loose	145	146	Cemente				
69.5 97	Tan clay		146		Sand & q				
97 114	Sand & gravel- clean,	small, loose							
111 116	Tan clay								
GONTPACTOR'S OR LANDOWNER'S CERTIFICATION. This water well was \(\big \) constructed. \(\big \) reconstructed, or \(\big \) plugged									
under my jurisdiction and was completed on (mo/day/year) 2-15-12									
This Water Well Record was completed on Imo/day/year)									
by (signature)									
Transport Control of the second of the secon									
1) 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Therefore the state of \$5.00 for each constructed well. Visit as at									
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									
KSA 82a-1212 Cneck: Winte Copy, Trink Copy									