	024 EDWA	RDS Q	raction ESE1/4	NE SE 1/4 SW	1/4 ; 35	.CTOIL WANDLE	:r ;			; Range ; R <b>18</b>	
	and direc	ction from neare	est town (	or city street	address of wel	l if locat	ed with:	in city?			
		BOWER!		040		Board o	f Agric	ulture, Di	vision o	f Water Re	sources
City, Sta	ate, ZIP (	code : KINSLE	EY, KS	67547-		Applica	tion Nu	mber:			
	SECTION	ATION WITH BOX:		DEPTH OF COMPLE Depth(s) Ground			'ATION: 1. 31	. ft.	2.	ft. 3	
1 1	: ; ; ;	: ! : !	1 1	LL'S STATIC WAT Pump te	ER LEVEL 31 stdata: Well					mo/day/yr urs pumpin	
1	) :	, NE	, ,	timated Yield	gpm: Well	water was		ft. after	ho	urs pumpin	g
₩ ;	<u>i</u>		-! E ! Boi	re Hole Diamete	er 8.75	in. to	80 ft.	, and	in. to	ft.	
; ; ;	1			LL WATER TO BE	USED AS: 01 DO	MESTIC					
		; SE ; ;		s a chemical/ba			mitted	to departa		•	
· }		<u>x</u>		yes, mo/day/yr	sample was su	bmitted			Water	well disin	fected?
Blank cas Casing he TYPE OF S	eight abov BCREEN OR	eter 5 ve land surface PERFORATION MAT TION OPENINGS AF	.12 in [ERIAL: 07	., weight 7 PVC	in. to lbs/ft.	ft., Wall thic	Dia kness or	in. to r gauge No	f 2. 26	t.	
Blank cas Casing he TYPE OF S BCREEN OR  BCREEN PE	eight abov SCREEN OR R PERFORAT ERFORATED	ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS:	12 in FERIAL: 07 RE: 08 From	., weight 7 PVC 3 SAW CUT 0 60 ft. to 1 ft. to	165/ft. 	Wall thic	kness or	r gauge No ft. ft.	f . 26	t. 	
Casing he TYPE OF S SCREEN OF SCREEN PE	eight abov SCREEN OR R PERFORAT ERFORATED	ve land surface PERFORATION MAT TION OPENINGS AF	12 in. FERIAL: 07 RE: 08 From From	, weight 7 PVC 3 SAW CUT 60 ft. to ft. to 25 ft. to	1bs/ft. 	Wall thic	to to	r gauge No	f . 26	t. 	
Blank cas Casing he FYPE OF S CCREEN OF GCREEN PE GRA GROUT MAT Grout Int Hat is t	eight abov SCREEN OR R PERFORATE ERFORATED WEL PACK FERIAL SERVALS:	ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS:  03 BENTONITE From 4 ft. st source of pos	12 in. FERIAL: 07 RE: 08 From From From From	y weight PVC S SAW CUT  60 ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	r gauge No ft. ft. ft.	ft.		
CREEN PE GRA GROUT MAT Grout Int irrection	ERIAL ERVEL PACK ETVALS:	ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS:  OS BENTONITE From 4 ft. st source of pos	12 in. FERIAL: 07 RE: 08 From From From From From From From From	y weight PVC S SAW CUT  60 ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	to to to	ft. ft. ft.	. <b>26</b>		
llank cas lasing he lasing	PERFORATED  AVEL PACK  ERFORATED  ERFORATED  ERFORATED  TO 1	ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS:  03 BENTONITE From 4 ft. st source of pos 11? N. E.	12 in. FERIAL: 07 RE: 08 From From From From From From From From	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
CREEN PE  GRA  GROUT MAT  FROM :  14 ;	PERFORATED  AVEL PACK  ERFORATED  ERFORATED  TO SERVE PACK  TO SER	PERFORATION MATERIAN OPENINGS AFTERVALS:  INTERVALS:  O3 BENTONITE From 4 ft. st source of postal? N. E. SILT & SAND BROWN CLAY GREY CLAY	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
CREEN PE  GRA  GROUT MAT  Grout Int  Gration  FROM ;  14 ;  21 ;	ERFORATED  AVEL PACK ERVALS: the neares from wel  14  21  46	PERFORATION MATERION OPENINGS AFTERVALS:  INTERVALS:  O3 BENTONITE From 4 ft. st source of postil? N. E.  SILT & SAND BROWN CLAY GREY CLAY O5 SAND AND 1	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
CREEN PE  GRA  GROUT MAT  FROM :  14 ;	ERFORATED  AVEL PACK ERVALS: the neares from wel  14  21  46	PERFORATION MATERION OPENINGS AFTER TO THE PERFORMANCE OF THE PERFORMA	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
Blank cas Casing he TYPE OF S SCREEN OF SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 14 ; 21 ; 46 ;	ERFORATED  ERFORATED  EVEL PACK  ERIAL  ERVALS:  TO  14  21  46  49	PERFORATION MATERION OPENINGS AFTER TO THE PERFORMANCE OF THE PERFORMA	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
Blank cas Casing he TYPE OF S SCREEN OF SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 14 ; 21 ; 46 ;	ERFORATED  ERFORATED  EVEL PACK  ERIAL  ERVALS:  TO  14  21  46  49	PERFORATION MATERION OPENINGS AFTER TO THE PERFORMANCE OF THE PERFORMA	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAW CUT  60 ft. to ft. to ft. to ft. to ft. to	80 ft., Fro ft., Fro ft., Fro ft., Fro	Wall thic	. to . to . to . to	ft. ft. ft.	. <b>26</b>	How many	
Blank cas Casing he TYPE OF S GCREEN OF GCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM   2   14   21   46   49	ERFORATED  AVEL PACK  ERFORATED  TO  2  14  21  46  49  80	PERFORATION MATERION OPENINGS AFTER TO THE PERFORMANCE OF THE PERFORMA	12 in. FERIAL: 07 RE: 08 From From From From From LITHOLO	y weight PVC SAN CUT  60 ft. to ft. to ft. to ft. to ft. From stamination: 01	80 ft., Fro ft., Fro 80 ft., Fro ft., Fro ft. to SEPTIC TANK	Wall thic  m ft  ft, F  FROM ;	to to to TO:	ft. ft. ft. ft.	ft.	How many G INTERVAL	