USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	T					
1. Locotion of well:	on of well: County Edwards Fraction 45E			Section number 36		Township number Range number
1. Locollon of wells	Kounna	1/4 1/4 1/4				T 25 S R 18 EM
2. Distance and dir	ection from pearest town or city:		3. Own	er of wel	ll:	Lloyd Derley
2. Distance and direction from nearest town or city: 125 34E 4n OFLewis Street address of well location if in city: 2. Distance and direction from nearest town or city: R.R. or				street:		
Street address of well location if in city: City, state, zip code:					Belpre, Ks.	
4. Locate with "X"	in section below:	Sketch map:	!			6. Bore hole dia. 16 in. Completion date
N						Well depth 73 ft. 4-15-76
						7 Cable tool _ Rotary _ Driven _ Dug
NW NE					Hollow rod Jetted Bored Reverse rotary	
						8. Use: Domestic Public supply Industry
					Irrigation Air conditioning Stock	
					Lawn Oil field water Other	
					9. Casing: Materiol Steel Height: (bove) or below	
					Threaded Welded Surface Su	
1 Mile					Dia. 16 in. to 23 ft. depth Wall Thickness: inches or	
5. Type and color of material				From	То	Dia in. to ft. depth gage No
						10. Screen: Manufacturer's name
Jandy	Tan Soil			1	1/2	WLR
	(0) -011			$\frac{\mathcal{O}}{\mathcal{O}}$,,	Type See Dia 16
Clay				1/2	//	Set between 43 ft. and 73 ft.
Cood	Gravel			11	20	ftandft.
GOOL	91000			//	35	Gravel pack?Size range of material 1/2 3/4 3/8
Clav				.35	42	11. Static water level: mo./day/yr.
				1/0		ft. below land surface Date
1900a	Gravel			42	73	12. Pumping level below land surfaces:
Hand	$C \setminus C \setminus$			73	16	ft. after hrs. pumping g.p.m g.p.m g.p.m.
(100100				/_	70	Estimated maximum yieldg.p.m.
						13. Water sample submitted: mo./day/yr.
						Yes No Date
						14. Well head completion:
			-			Pitless adapter Inches above grade
						15. Well grouted?
						With: Neat cement Bentonite Concrete Depth: From ft. to ft.
						16. Nonrest source of possible contamination: ft Direction Type Corral
						Well disinfected upon completion? Yes No
						17. Pump:
						Manufacturer's name WLR Model number 3- MS-12 HP 80 Volts
						Length of drop pipe 50 ft. capacity 200 g.p.m.
						Туре:
						SubmersibleTurbine
	(Use a second she	eet if needed)	ľ			Jet Reciprocating Centrifugal Other
18. Elevation:	19. Remarks:	,	l			-
						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report
						is true to the best of my knowledge and belief.
Topography: Hill						Rosencrantz-Bens 134 51.
Slope_					l	Business name (2 reat Bounds Ke
Upland						Address Address Charles Charles
Valley						Authorized representative Date