WATER WELL RECORD Form WWC-5 KSA 82a-1212

COUNTY: Edwar	WELL: ; Frac do ; NE	tion 1/4 NE 1/4 SW	Sect: 1/4 12	ion Number	† Township No † T 25			
Distance and direct 1 1/2 S. 2 1/2 E.		town or city stree	et address of well	if located wi	thin city?			
WATER WELL OWNER: RR#, St. Address,	Box # : 411 E. 4	TĤ		Board of Agr	iculture, Divi	sion of Wat	er Resource	?S
City, State, ZIP o	code : KI NSLEY ,	KS 67547-		Application	Number:			
	ATION WITH	; 4 DEPTH OF COMP ; Depth(s) Grou	PLETED WELL 100		-	ft.	3.	ft.
\			WATER LEVEL 64 testdata: Well wa				• •	gpi
1 ; NW ; ; ;	• - •	Estimated Yield	i gpm: Well i	water was	ft. after	hours f	pumping	gpi
		E : Bore Hole Diame			t., and	in. to	ft.	
	; SE;	•						
1 ! !		Was a chemical/ If yes, mo/day/ 				•	disinfected	1? Ye i
Casing height abov	ve land surface	. to 80 ft., Di 12 in., weigh	(NG JOINTS: GLUED ia in. to nt lbs/ft. N					
Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORAT SCREEN PERFORATED	ve land surface PERFORATION MATER TION OPENINGS ARE:	. to 80 ft., Di 12 in., weigh IAL: 07 PVC 08 SAW CUT From 80 ft. t	ia in. to it lbs/ft. i	Wall thickness	or gauge No.			
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORAT SCREEN PERFORATED	ve land surface PERFORATION MATER TION OPENINGS ARE:	. to 80 ft., Di 12 in., weigh IAL: 07 PVC 08 SAW CUT From 80 ft. t	to 100 ft., From to 100 ft., From to 100 ft., From	Wall thickness ft. to ft. to ft. to	or gauge No. ft. ft.			
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE SCREEN PERFORATED GRAVEL PACK GROUT MATERIAL Grout Intervals:	ve land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi	. to 80 ft., Di 12 in., weigh IAL: 07 PVC	ia in. to lbs/ft. i 100 ft., From to 100 ft., From to ft., From ft. to	Wall thickness ft. to ft. to ft. to	ft. ft. ft. ft.	26	many feet?	
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATED SCREEN PERFORATED GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from well FROM TO 18	ve land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi 11? ALL SILT & SAND	. to 80 ft., Di 12 in., weigh IAL: 07 PVC	ia in. to ht lbs/ft. i to 100 ft., From to ft., From to 100 ft., From to ft., From CATTLE PASTURE	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	26		:
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel FROM : TO : 18 : 18 : 48 : 48 : 61 :	VE land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi il? ALL SILT & SAND TAN CLAY O5 SAND AND 17	to 80 ft., Di 12 in., weigh 1AL: 07 PVC 08 SAW CUT From 80 ft. t From ft. t From ft. t From ft. t LITHOLOGIC LOG	ia in. to ht lbs/ft. i to 100 ft., From to ft., From to 100 ft., From to ft., From CATTLE PASTURE	ft. to ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.		
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE SCREEN PERFORATED SRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel FROM	ve land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi il? ALL SILT & SAND TAN CLAY	to 80 ft., Di 12 in., weigh 1AL: 07 PVC 08 SAW CUT From 80 ft. t From ft. t From 25 ft. t From ft. t 25 ft., From ble contamination: LITHOLOGIC LOG	ia in. to ht lbs/ft. i to 100 ft., From to ft., From to 100 ft., From to ft., From CATTLE PASTURE	ft. to ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.		
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel FROM	VE land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi 11? ALL SILT & SAND TAN CLAY O5 SAND AND 17 TAN CLAY	to 80 ft., Di 12 in., weigh 1AL: 07 PVC 08 SAW CUT From 80 ft. t From ft. t From 25 ft. t From ft. t 25 ft., From ble contamination: LITHOLOGIC LOG	ia in. to ht lbs/ft. i to 100 ft., From to ft., From to 100 ft., From to ft., From CATTLE PASTURE	ft. to ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.		
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel FROM	VE land surface PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi 11? ALL SILT & SAND TAN CLAY O5 SAND AND 17 TAN CLAY	to 80 ft., Di 12 in., weigh 1AL: 07 PVC 08 SAW CUT From 80 ft. t From ft. t From 25 ft. t From ft. t 25 ft., From ble contamination: LITHOLOGIC LOG	ia in. to ht lbs/ft. i to 100 ft., From to ft., From to 100 ft., From to ft., From CATTLE PASTURE	ft. to ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.		
Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel FROM	PERFORATION MATER TION OPENINGS ARE: INTERVALS: O3 BENTONITE From 1 ft. to st source of possi 11? ALL SILT & SAND TAN CLAY O5 SAND AND 17 TAN CLAY O5 SAND AND 17	to 80 ft., Di 12 in., weigh 1AL: 07 PVC 08 SAW CUT From 80 ft. t From ft. t From 25 ft. t From ft. t 25 ft., From ble contamination: LITHOLOGIC LOG	ia in. to it lbs/ft. i to 100 ft., From to ft., From to ft., From to ft. to CATTLE PASTURE	ft. to ft. to ft. to ft. to ft. TO	ft. ft. ft. ft. jurisdiction a	ft. How PLUGGING INT		