					1/4 SE		Section N					
	e and dire KINSLEY,		nearest	town or	city street	address o	of well if l	ocated wi	thin city?			
		Box # :		NARI	286		§oa	erd of Agr.	iculture, Di	ivision of	₩ater Re	sourc <i>e</i> s
City, St	ate, ZIP	code :	KINSLEY,	KS (67547-		Арр	lication 1	∀umber:			
					PTH OF COMPL pth(s) Groun					2. 0	ft. 3.	. 0 ft
1 1	[] }	: : : : : : : : :	1 6	i	'S STATIC WA Pump t		16 ft. b Well water				mo/day/yr rs pumping	
	Me	,		,	mated Yield	O gpm:	: Well water	was () ft. after	0 hou	rs pumping	g Ogs
	·¦	¦x	<u> </u>	E ¦ Bore	Hole Diamet	er	8.75 in. t	o 70 f	t., and	in. to	0 ft.	
		i i	: : :	WELL	WATER TO BE	USED AS:	01 DOMESTIC	:				
1									i to denartm	iont? No :		
TYPE OF Blank ca Casing h	BLANK CAS sing diam eight abo	¦¦- ING USED: (eter ; ve land su	 02 PVC 5 in rface	. to 3	a chemical/b es, mo/day/y CASIN 32 ft., Dia weight	IG JOINTS:	GLUED to 0 f	t., Dia	in. to	 o 0 ft		fected? Yı
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORA	¦¦- ING USED: (eter !	02 PVC 5 in rface DN MATER NGS ARE:	. to 3 12 in., IAL: 07 F 08 S	CASIN 32 ft., Dia weight PVC BAN CUT	IG JOINTS: in. 0 lbs	GLUED to Off s/ft. Wall	t., Dia thickness	in. to or gauge No	 o 0 ft		fected? Ye
TYPE OF Blank ca Casing h TYPE OF SCREEN OF	BLANK CAS sing diam eight abo SCREEN OR R PERFORA	ING USED: (eter ; ve land sui PERFORATIO	02 PVC 5 in rface DN MATER NGS ARE:	. to 3 12 in., IAL: 07 F 08 S	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to	JG JDINTS: in. 0 lbs 52 ft. 0 ft. 52 ft.	GLUED to 0 f 5/ft. Wall , From	t., Dia thickness Oft. to Oft. to	in. to or gauge No	 o 0 ft		fected? Ye
Blank ca Casing h TYPE OF: SCREEN OF: SCREEN PI GROUT MA GROUT MA Grout In What is	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK	ING USED: (eter ! ve land sur PERFORATION TION OPENIN INTERVALS: INTERVALS: 03 BENTON: From 4	DN MATER NGS ARE: :	. to 3 12 in., IAL: 07 F 08 S From From From From 25 ft	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to	52 ft. 0 ft. to	GLUED to Of ft. Wall From From From From From	t., Dia thickness Oft. to Oft. to	in. to or gauge No 0 ft. 0 ft. 0 ft.	 o 0 ft		fected? Ye
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN P GROUT MA GROUT IN What is Direction	BLANK CAS sing diam reight abo SCREEN OR R PERFORA ERFORATED MAVEL PACK TERIAL ttervals: the neare of from we	ING USED: (eter ! ve land sur PERFORATION TION OPENIN INTERVALS: O3 BENTON: From st source (11? SE	02 PVC 5 in rface ON MATER NGS ARE: :	. to 3 12 in., IAL: 07 F 08 S From From From From From	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to 0 ft. to	52 ft. 0 ft. to	GLUED to Off fft. Wall From From From From From From From	t., Dia thickness Oft. to Oft. The Oft.	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN OF GROUT MA GROUT MA Grout In What is Direction FROM ; O ;	BLANK CAS using diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare from we	ING USED: (eter ! ve land sui PERFORATION TION OPENI) INTERVALS: INTERVALS: 03 BENTON: From ! st source (11? SE ! SILT & S	DO2 PVC in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 3 12 in., IAL: 07 F 08 S From From From From LITHOLOGI	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to 0 ft. to	52 ft. 0 ft. to	GLUED to Of ft. Wall From From From From From	t., Dia thickness Oft. to Oft. The Oft.	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.		feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN P GROUT MA GROUT MA Grout In What is Direction	BLANK CAS using diam eight abo SCREEN OR R PERFORATED ERFORATED AVEL PACK STERIAL ttervals: the neare in from we	ING USED: (eter ! ve land sui PERFORATION TION OPENI) INTERVALS: INTERVALS: 03 BENTON: From ! st source (11? SE ! SILT & S	D2 PVC in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 3 12 in., IAL: 07 F 08 S From From From From LITHOLOGI	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to 0 ft. to	52 ft. 0 ft. to	GLUED to Off fft. Wall From From From From From From From	t., Dia thickness Oft. to Oft. The Oft.	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.	How many t	feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN OF GROUT MA GROUT IN What is Direction FROM ; 0 ; 2 ;	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare on from we	ING USED: (eter !: ve land sui PERFORATION OPENI) INTERVALS: INTERVALS: 03 BENTON: From : st source (11? SE : SILT & S: : 05 SAND	D2 PVC in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 3 12 in., IAL: 07 F 08 S From From From From LITHOLOGI	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to 0 ft. to	52 ft. 0 ft. to	GLUED to Off fft. Wall From From From From From From From	t., Dia thickness Oft. to Oft. The Oft.	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.	How many t	feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN OF GROUT MA GROUT IN What is Direction FROM ; 0 ; 2 ;	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare on from we	ING USED: (eter !: ve land sui PERFORATION OPENI) INTERVALS: INTERVALS: 03 BENTON: From : st source (11? SE : SILT & S: : 05 SAND	D2 PVC in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 3 12 in., IAL: 07 F 08 S From From From From LITHOLOGI	CASIN 32 ft., Dia weight PVC SAN CUT 32 ft. to 0 ft. to 25 ft. to 0 ft. to	52 ft. 0 ft. to	GLUED to Off fft. Wall From From From From From From From	t., Dia thickness Oft. to Oft. The Oft.	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.	How many t	feet?

completed on (mo/day/year) 10/22/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224
This Water Well Record was completed on (mo/day/yr) 12/17/94
under the business name of CARL HAYSE WATER WELL SVC
by (signature)