


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction: <u>NW 1/4 NW 1/4 NW 1/4</u> Section: <u>1</u> Township: <u>25</u> S Range: <u>2</u> E <u>(W)</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>	
2 WATER WELL OWNER: <u>Mike Sharp</u> RR#, St. Address, Box #: <u>12530 135th West</u> City, State, ZIP Code: <u>Bentley, KS 67016</u> Board of Agriculture, Division of Water Resources Application Number: <u>80</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: <u>8/30/95</u> Depth(s) Groundwater Encountered: <u>32</u> ft. 2. <u>32</u> ft. 3. <u>8/30/95</u> ft. WELL'S STATIC WATER LEVEL: <u>32</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>30</u> ft. after <u>80</u> hours pumping <u>30</u> gpm Est. Yield <u>30</u> gpm Well water was <u>80</u> ft. after <u>80</u> hours pumping <u>30</u> gpm Bore Hole Diameter: <u>11</u> in. to <u>80</u> ft. and <u>80</u> in. to <u>80</u> ft. WELL WATER TO BE USED AS: 1 Domestic <u>(X)</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>
5 TYPE OF BLANK CASING USED: 1 Steel <u>(X)</u> 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 2 PVC <u>(X)</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter: <u>5</u> in. to <u>70</u> ft. Dia. <u>2.60</u> in. to <u>70</u> ft. Dia. <u>160</u> PSI Casing height above land surface: <u>12</u> in., weight <u>2.60</u> lbs./ft. Wall thickness or gauge No. <u>160</u> PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) <u>7 PVC</u> 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot <u>(X)</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) <u>80</u> SCREEN-PERFORATED INTERVALS: From <u>70</u> ft. to <u>80</u> ft., From <u>70</u> ft. to <u>80</u> ft., From <u>70</u> ft. to <u>80</u> ft. GRAVEL PACK INTERVALS: From <u>35</u> ft. to <u>80</u> ft., From <u>35</u> ft. to <u>80</u> ft., From <u>35</u> ft. to <u>80</u> ft.	
6 GROUT MATERIAL: 1 Neat cement 3 Cement grout 5 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>28</u> ft., From <u>3</u> ft. to <u>28</u> ft., From <u>3</u> ft. to <u>28</u> ft. What is the nearest source of possible contamination: 1 Septic tank <u>(X)</u> 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>Northeast</u> How many feet? <u>100</u>	
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 2 Top Soil	
2 24 clay	
24 34 fine sand	
34 48 clay	
48 80 fine to med. sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>8-30-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>9-1-95</u> under the business name of <u>Weninger Drilling</u> by (signature) <u>Karina Morrissey</u>	