

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 SW 1/4	Section Number 13	Township Number T 25 S	Range Number R 2W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?


Lot 7, 12800 W. 104th N. (Bentley Farms Add.) Bentley, KS.

WATER WELL OWNER: **ROACH, James**
 RR#, ST. ADDRESS, BOX #: **12800 W. 104th N.**
 CITY, STATE, ZIP CODE: **Bentley, Kansas**

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 55 ft.	ELEVATION: 04/28/1997
Depth(s) groundwater Encountered 1 ft.	2 ft.
WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr
Pump test data:	
Well water was	ft. after
hours pumping	gpm
Est. Yield	gpm: Well water was
ft. after	hours pumping
gpm	gpm
Bore Hole Diameter 12 in. to 55 ft. and	in. to
WELL WATER TO BE USED AS:	
5 Public water supply	8 Air conditioning
11 Injection well	
1 Domestic	3 Feedlot
6 Oil field water supply	9 Dewatering
12 Other (Specify below)	
2 Irrigation	4 Industrial
7 Lawn and garden only	10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes	No ☒ ; If yes, mo/day/yr sample was
submitted	Water Well Disinfected? Yes ☒ No

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued ☒ Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded
2 PVC	4 ABS	7 Fiberglass	SDR-26	Threaded
Blank casing Diameter 5 in. to 35 ft., Dia	in. to	ft., Dia	in. to	ft.
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATION INTERVALS:	from 35 ft. to 55 ft., From	ft. to	ft.	
	from	ft. to	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24 ft. to 65 ft., From	ft. to	ft. to	ft.
	from	ft. to	ft. to	ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft. From		ft. to	ft. From	ft. to
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None Apparent

Direction from well?	How many feet?
FROM	TO
0	2
2	10
10	23
23	25
25	35
35	55
LITHOLOGIC LOG	PLUGGING INTERVALS
topsoil	
clay	
medium sand	
clay	
medium sand	
fine sand with clay	
grey in color	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **04/28/1997** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **236** This Water Well Record was completed on (mo/day/yr) **04/30/97**

Under the business name of **Harp Well & Pump Service, Inc.** by (signature)

Todd S. Harp