

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SE 1/4 NE 1/4 NE 1/4</u>	<u>13</u>	T <u>250</u> S	R <u>2</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>10701 W. 119th N.</u>					
2 WATER WELL OWNER: <u>Jim & Rhonda Rueger</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>309 Everett</u>		Application Number:			
City, State, ZIP Code: <u>Wadell KS 67146</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>41</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered: 1. <u>16</u> ft. 2. <u>41</u> ft. 3. <u>6-17-97</u> ft.			
		WELL'S STATIC WATER LEVEL: <u>16</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>20</u> ft. after <u>11</u> hours pumping <u>41</u> gpm			
		Est. Yield <u>20</u> gpm Well water was <u>41</u> ft. after <u>11</u> hours pumping <u>41</u> gpm			
		Bore Hole Diameter: <u>11</u> in. to <u>41</u> ft. and <u>41</u> in. to <u>41</u> ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 8 Air conditioning ☐ 11 Injection well ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 9 Dewatering ☐ 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
☒ 1 Steel ☐ 3 RMP (SR) ☒ 2 PVC ☐ 4 ABS		☐ 5 Wrought iron ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ 7 Fiberglass ☐ 8 Concrete tile ☐ 10 Asbestos-cement ☐ 11 Other (specify) ☐ 12 None used (open hole)			
Blank casing diameter <u>5</u> in. to <u>31</u> ft. Dia. <u>2.40</u> in. to <u>100PST</u> ft.					
Casing height above land surface: <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>100PST</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify) ☐ 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:					
From <u>31</u> ft. to <u>41</u> ft. From <u>16</u> ft. to <u>41</u> ft.					
GRAVEL PACK INTERVALS:					
From <u>16</u> ft. to <u>41</u> ft. From <u>16</u> ft. to <u>41</u> ft.					
6 GROUT MATERIAL:					
☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other					
Grout intervals: From <u>3</u> ft. to <u>16</u> ft. From <u>16</u> ft. to <u>41</u> ft.					
What is the nearest source of possible contamination:					
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)					
Direction from well? <u>South</u>		How many feet? <u>100</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	top soil			
8	36	fine to medium sand			
36	41	clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-17-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>6-18-97</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Nichole Becker</u>					