

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SW 1/4 SE 1/4 SW 1/4</u>	<u>2</u>	T <u>25</u> S	R <u>2</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>14400 W. 117th N. Bently, KS. 67016</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : <u>14400 W. 117th N.</u>		Application Number:			
City, State, ZIP Code : <u>Bently, KS. 67016</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>70</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL <u>26</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>50</u> gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS:			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
<u>2 PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter <u>5"</u> in. to <u>60</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>13"</u> in., weight <u>2.4</u> lbs./ft. Wall thickness or gauge No. <u>100 PSI</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		<u>3 Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>70</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>26</u> ft. to <u>70</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>26</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
<u>1 Septic tank</u>		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>East</u>		How many feet? <u>65'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	20	Clay			
20	35	Coarse Sand			
35	50	Clay			
50	70	Med Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-6-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>H740</u> This Water Well Record was completed on (mo/day/yr) <u>3-10-05</u> under the business name of <u>Wininger Drilling Inc.</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					