

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgwick SE</u> <u>SE 1/4 SE 1/4 NE 1/4</u>		<u>1314</u>		T <u>25</u> S		R <u>2</u> <u>EW</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>13611 W. 105th St, Bentley</u>							
2 WATER WELL OWNER: <u>Malone Const.</u>							
RR#, St. Address, Box # : <u>13611 W. 105th St.</u>				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : <u>Bentley, KS 67016</u>				Application Number:			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL		5 ELEVATION:			
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered		ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL		ft. below land surface measured on mo/day/yr <u>10/26/05</u>			
		Pump test data: Well water was		ft. after hours pumping gpm			
		Est. Yield gpm: Well water was		ft. after hours pumping gpm			
		Bore Hole Diameter. in. to ft., and in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation		4 Industrial		7 Domestic (lawn & garden)		10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒		If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
				7 Fiberglass		CASING JOINTS: Glued. ☒ Clamped.	
Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.						Welded	
Casing height above land surface. 16 in., weight 160 lbs./ft. Wall thickness or gauge No. 26						Threaded.	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes	
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify) ft.	
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 24 ft. to 40 ft., From ft. to ft.							
6 GROUT MATERIAL:							
1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
Direction from well? <u>South</u>						How many feet? <u>70'</u>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	2	TOP SOIL					
2	14	Clay					
14	31	med sand					
31	40	Coarse Sand gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/26/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 1611 This Water Well Record was completed on (mo/day/yr) 11/15/05 under the business name of <u>Chase Drilling</u> by (signature) <u>O. Chase</u>							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							