

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Bedford

Fraction

NW 1/4 NW 1/4 SW 1/4

Section Number

34

Township Number

T

25

S

Range Number

R

2

E/W

0

Distance and direction from nearest town or city street address of well if located within city?

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: _____

Longitude: _____

Elevation: _____

Datum: _____

Data Collection Method: _____

2 WATER WELL OWNER:

RR#, St. Address, Box # : 5150 N 167th WCity, State, ZIP Code : Colwell, KS 67030

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

	-- NW --	-- NE --	
W	X		E
	-- SW --	-- SE --	

S

4 DEPTH OF COMPLETED WELL 20 ft.

Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.

WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yrSample was submitted Water well disinfected? Yes ☒ No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

5 Wrought Iron

8 Concrete tile

CASING JOINTS: Glued ☒ Clamped☒ PVC 4 ABS

6 Asbestos-Cement

9 Other (specify below)

Welded

7 Fiberglass

Threaded

Blank casing diameter 5 in. to 29 ft., Diameter in. to ft., Diameter in. to ft.Casing height above land surface 12 in., Weight 2.40 lbs./ft. Wall thickness or gauge No. 140,021

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless Steel

5 Fiberglass

☒ PVC

9 ABS

11 Other (Specify)

2 Brass

4 Galvanized Steel

6 Concrete tile

8 RM (SR)

10 Asbestos-Cement

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

☒ Mill slot

5 Gauzed wrapped

7 Torch cut

9 Drilled holes

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

8 Saw Cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 79 ft. to 90 ft., From ft. to ft.From 19 ft. to 90 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

☒ Bentonite

4 Other

Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

13 Insecticide Storage

16 Other (specify

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

14 Abandoned water well

below)

☒ Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer Storage

15 Oil well/gas well

Direction from well? North eastHow many feet? 100 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	10	Clay			
10	18	Fine Sand			
18	35	Med Sand			
35	45	Fine Sand			
45	60	Med Sand			
60	75	Clay			
75	90	Med Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 1-11-20 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 740 This Water Well Record was completed on (mo/day/year) 11-2-06 under the business name of Weninger Drilling Inc by (signature) [Signature]INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdhe.state.ks.us/geo/waterwells>.