

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County <u>Ledgewick</u> Fraction <u>SW 1/4 SW 1/4 NW 1/4</u> Section number <u>6</u> Township number <u>T 25 S</u> Range number <u>R 2 E</u>	
2. Distance and direction from nearest town or city: <u>4 W Bentley KS, 1 1/2 North</u> Street address of well location if in city:	
3. Owner of well: <u>Sherman G. Sperry</u> R.R. or street: <u>303 Wheatland Place</u> City, state, zip code: <u>Wichita KS 67235</u>	
4. Locate with "X" in section below: Sketch map: N W X E S 1 Mile well X Septic	
5. Type and color of material	
Top soil	0 2
red clay	2 12
fine sand	12 18
red clay	18 21
med sand	21 33
red clay	33 34
med. gravel	34 50
6. Bore hole dia. <u>11</u> in. Completion date <u>12/30/78</u> Well depth <u>50</u> ft.	
7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Law ☐ Oil field water ☐ Other	
9. Casing: Material <u>Steel</u> Height Above or below Threaded ☐ Welded ☒ Surface <u>12</u> in. RMP ☒ PVC ☐ Weight <u>1.50</u> lbs./ft. Dia. <u>5</u> in. <u>50</u> ft. depth Wall Thickness: inches or Dia. <u>5</u> in. to <u>50</u> ft. depth gage No. <u>1200</u>	
10. Screen: Manufacturer's name <u>Sunflower</u> Type <u>200</u> Dia. <u>5 in</u> Slot gauze <u>1/16</u> Length <u>10 ft</u> Set between <u>40</u> ft. and <u>50</u> ft. Gravel pack? <u>yes</u> size range of material <u>3/8</u>	
11. Static water level: <u>16</u> ft. below land surface Date <u>12/30/78</u> mo./day/yr.	
12. Pumping level below land surfaces: <u>17</u> ft. after <u>1/2</u> hrs. pumping <u>20</u> g.p.m. <u>17</u> ft. after <u>1/2</u> hrs. pumping <u>20</u> g.p.m. Estimated maximum yield <u>100</u> g.p.m.	
13. Water sample submitted: <u>Yes</u> ☒ No ☐ Date <u>12/30/78</u> mo./day/yr.	
14. Well head completion: ☒ Pitless adapter <u>12</u> inches above grade	
15. Well grouted? <u>yes</u> With: <u>Neat cement</u> ☐ Bentonite ☒ Concrete Depth: From <u>3</u> ft. to <u>13</u> ft.	
16. Nearest source of possible contamination: ft. <u>150</u> Direction <u>East</u> Type <u>Septic</u> Well disinfected upon completion? ☒ Yes ☐ No	
17. Pump: <u>Not installed</u> Manufacturer's name <u>TXW</u> Model number <u>18035</u> HP <u>3/4</u> Volts <u>220</u> Length of drop pipe <u>30</u> ft. capacity <u>15</u> g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
(Use a second sheet if needed)	
18. Elevation: Topography: ☐ Hill ☒ Slope ☒ Upland ☐ Valley	19. Remarks: <u>Customer to furnish 4'x4'x4'</u> <u>slab around well at grade</u> <u>Per State Regulations</u> <u>signed X Sherman G. Sperry</u>
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Business name <u>Wenger Dilling</u> 318 Address <u>Edwicks KS</u> License No. <u>12/30/78</u> Signed <u>[Signature]</u> Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5