

1 LOCATION OF WATER WELL		Fraction NE 1/4 SE 1/4 SW 1/4		Section Number 11		Township Number T 25 S		Range Number R 2 E W	
County: Sedgewick Distance and direction from nearest town or city street address of well if located within city? 209 Rhodes Bentley KS.									
2 WATER WELL OWNER: Glenn Simon RR#, St. Address, Box #: 209 Rhodes Bentley KS 67016. City, State, ZIP Code:						Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 13 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 6-7-83. Pump test data: Well water was 13 ft. after 1/2 hours pumping 20 gpm Est. Yield 60 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 40 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic3 Feedlot5 Public water supply8 Air conditioning11 Injection well 2 Irrigation4 Industrial6 Oil field water supply9 Dewatering12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 5 in. to 30 ft., Dia. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26			3 Wrought iron 6 Asbestos-Cement 7 Fiberglass CASING JOINTS: Glued X Clamped Welded Threaded. 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft.			3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)						
GRAVEL PACK INTERVALS: From 13 ft. to 40 ft.									
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 3 ft. to 13 ft.			2 Cement grout 3 Bentonite 4 Other What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)						
Direction from well? North			How many feet? 25						
FROM TO LITHOLOGIC LOG			FROM TO LITHOLOGIC LOG						
0 2 Top soil									
2 11 Red clay									
11 29 med Sand									
29 30 clay									
30 40 gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-7-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-7-83 under the business name of Weninger Pumping by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66628. Send one to WATER WELL OWNER and retain one for your records.									