

1 LOCATION OF WATER WELL: Fraction 1/4 1/4 1/4 1/4 Section Number Township Number Range Number
County: Sedgewick SW SE NW T 25 S R 2 EW
Distance and direction from nearest town or city street address of well if located within city?
100 Rogers Bentley KS
2 WATER WELL OWNER: 4141 W. Black Valley Center
RR#, St. Address, Box #: 408 Cedarcrest
City, State, ZIP Code: 67147
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the center section, labeled NW, NE, SW, SE, and a 1-mile scale bar.]
4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 627-84
Depth(s) Groundwater Encountered 1. 13 ft. 2. 14 ft. 3. 20 ft.
WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 6-27-84
Pump test data: Well water was 14 ft. after 20 hours pumping 20 gpm
Est. Yield 50 gpm: Well water was 14 ft. after 20 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 35 ft., and 11 in. to 35 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter 5 in. to 25 ft., Dia 1.59 in. to 25 ft., Dia 25 ft.
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 26
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABC 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft., From 25 ft. to 35 ft., From 25 ft. to 35 ft.
GRAVEL PACK INTERVALS: From 13 ft. to 35 ft., From 13 ft. to 35 ft., From 13 ft. to 35 ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 35 ft., From 13 ft. to 35 ft., From 13 ft. to 35 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage ph 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? South How many feet? 25
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0-2 top soil
2-12 clay
12-35 fine to med sand
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-27-84 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-5-84
under the business name of Weninger Bentley by (signature) [Signature]
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.