

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 11 Township Number T 25 S Range Number R 2 W
 County: Edgewood
 Distance and direction from nearest town or city street address of well if located within city?
See Below.

2 WATER WELL OWNER: GARY WILSON
 RR#, St. Address, Box #: 300 N. Phelps
 City, State, ZIP Code: BENTLEY KS 67016
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W			
E			
S			

4 DEPTH OF COMPLETED WELL: 72 ft. ELEVATION: 2828 ft. below land surface measured on 4/21/90
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 28 ft.
 WELL'S STATIC WATER LEVEL 2828 ft. below land surface measured on 4/21/90
 Pump test data: Well water was 28 ft. after 2 hours pumping 280 gpm
 Est. Yield 100 gpm: Well water was 28 ft. after 2 hours pumping 280 gpm
 Bore Hole Diameter 11 in. to 72 ft. and 72 in. to 72 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☒ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 62 ft. Dia. 2 in. to 40 ft. Dia. 160-AST
 Casing height above land surface 12 in., weight 240 lbs./ft. Wall thickness or gauge No. 160-AST
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) X
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot ☒ 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) X
 SCREEN-PERFORATED INTERVALS: From 62 ft. to 72 ft. From 62 ft. to 72 ft.
 From 62 ft. to 72 ft. From 62 ft. to 72 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 72 ft. From 23 ft. to 72 ft.
 From 23 ft. to 72 ft. From 23 ft. to 72 ft.

6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other X
 Grout Intervals: From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
☒ 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
☒ 3 Watertight sewer lines 6 Sewage pit 9 Feedyard 13 Insecticide storage
 Direction from well? North How many feet? 15 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top so.	58	59	clay
2	14	clay	59	72	gravel
14	29	fine sand			
29	31	clay			
31	36	SAND			
36	51	clay			
51	58	fine sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-21-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 The Water Well Record was completed on (mo/day/yr) 4-25-90 under the business name of Weninger Dull by (signature) Weninger Dull

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4