


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SW 1/4 Section Number 11 Township Number T 25 S Range Number R 2 E W
 County: Sedgewich
 Distance and direction from nearest town or city street address of well if located within city: 214 York St Bentley KS

2 WATER WELL OWNER: Fidelity Investment
 RR#, St. Address, Box #: 100 E. English Wichita KS 67202
 City, State, ZIP Code: Wichita KS 67202
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 22 ft. below land surface measured on mo/day/yr 6-20-90
 Depth(s) Groundwater Encountered 1. 22 ft. 2. 22 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 6-20-90
 Pump test data: Well water was 22 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 60 gpm: Well water was 22 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 36 ft. and 36 in. to 36 ft.
 WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 26 ft. Dia. 1.59 lbs./ft. Wall thickness or gauge No SOR-26
 Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No SOR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 36 ft. From 23 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 36 ft. From 36 ft. to 36 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Wastewater sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? North How many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	16	clay			
16	22	fine sand			
22	23	clay			
23	36	sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-20-90 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 6318 This Water Well Record was completed on (mo/day/yr) 6-25-90
 under the business name of Wenger Dully by (signature) Wenger