

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County <u>Sedgwick</u>	Fraction <u>center of</u> 1/4 1/4 NW/4	Section number <u>12</u>	Township number T <u>25</u> S R <u>2</u> E <u>10</u>	Range number
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>1 E., 1 N. Bentley</u>			3. Owner of well: <u>Jay Ramsey</u> R.R. or street: City, state, zip code: <u>Sedgwick, Kans.</u>			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: <u>open field</u>		6. Bore hole dia. <u>30</u> in. Completion date <u>1/14/77</u> Well depth <u>84</u> ft.		
		7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary				
		8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other				
		9. Casing: Material <u>C-112</u> Height: Above or below Threaded ☐ Welded ☐ Surface <u>12</u> in. RMP ☐ PVC ☐ Weight ☐ lbs./ft. Dia. <u>16</u> in. to <u>84</u> ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. <u>3/4"</u>				
		10. Screen: Manufacturer's name <u>Johnson</u> Type <u>cem-ash</u> Dia. <u>16"</u> Slot/gauze <u>1/4"</u> Length <u>26'</u> Set between <u>58'</u> ft. and <u>84'</u> ft. ☐ ft. and ☐ ft. Gravel pack? ☒ Size range of material <u>3/8</u>				
5. Type and color of material		From	To	11. Static water level: <u>18</u> ft. below land surface Date <u>1/12/77</u> mo./day/yr.		
<u>Topsoil</u>		<u>0</u>	<u>1</u>	12. Pumping level below land surfaces: <u>25</u> ft. after <u>1</u> hrs. pumping <u>800</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>900</u> g.p.m.		
<u>Gray clay and sand</u>		<u>1</u>	<u>10</u>	13. Water sample submitted: <u> </u> mo./day/yr. Yes ☐ No ☒ Date <u> </u>		
<u>Fine sand</u>		<u>10</u>	<u>25</u>	14. Well head completion: ☐ Pitless adapter <u>12</u> Inches above grade		
<u>Med. sand</u>		<u>25</u>	<u>35</u>	15. Well grouted? ☒ With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.		
<u>Clay</u>		<u>35</u>	<u>55</u>	16. Nearest source of possible contamination: ft. <u>34 mi</u> Direction <u>S</u> Type <u>Dam</u> Well disinfected upon completion? ☐ Yes ☒ No		
<u>Gravel - Fair to Good</u>		<u>55</u>	<u>84</u>	17. Pump: ☐ Not installed Manufacturer's name <u>Peerless</u> Model number <u>6942</u> HP <u>30</u> Volts <u> </u> Length of drop pipe <u>70</u> ft. capacity <u>900</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
<u>Clay</u>		<u>84</u>	<u>95</u>	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Weninger Irrigation 238</u> Business name <u>Maize</u> License No. <u> </u> Address <u> </u> Signed <u>H. Weninger</u> Date <u>2/14/77</u> Authorized representative		
18. Elevation:		(Use a second sheet if needed)		19. Remarks:		
Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5