


1 LOCATION OF WATER WELL: Sedgwick	FRACTION 1/4 NEAR CENTER OF 1/4 SE 1/4	Section Number 23	Township Number T 25 S	Range Number R 2W E/W																																																																																																
Distance and direction from nearest town or city street address of well if located within city? 2 miles South, 3/4 East, 1/4 North of Bentley, Kansas																																																																																																				
2 WATER WELL OWNER: SEILER FARMS RR#, ST. ADDRESS, BOX #: Rt. 3 Box 69 CITY, STATE, ZIP CODE: Valley Center, Kansas 67147		Board of Agriculture, Division of Water Resource Application Number: 26,436																																																																																																		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 200 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 24 FT. BELOW LAND SURFACE MEASURED ON 06/14/1994 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 850 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 200 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																																																																			
	5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass Threaded Blank casing Diameter 16 in. to 100 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 19.750 lbs. / ft. Wall thickness or gauge No. .616 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																																																																																			
	SCREEN-PERFORATION INTERVALS: from 100 ft. to 160 ft., From ft. to ft. from 180 ft. to 200 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 200 ft., From ft. to ft. from ft. to ft., From ft. to ft.																																																																																																			
	6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>topsoil</td><td></td><td></td><td></td></tr> <tr><td>2</td><td>35</td><td>coarse sand and gravel</td><td></td><td></td><td></td></tr> <tr><td>35</td><td>40</td><td>tan clay</td><td></td><td></td><td></td></tr> <tr><td>40</td><td>60</td><td>fine to coarse sand and</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>fine to medium gravel</td><td></td><td></td><td></td></tr> <tr><td>60</td><td>70</td><td>sandy tan clay</td><td></td><td></td><td></td></tr> <tr><td>70</td><td>80</td><td>fine to coarse sand and</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>fine to medium gravel</td><td></td><td></td><td></td></tr> <tr><td>80</td><td>105</td><td>tan clay</td><td></td><td></td><td></td></tr> <tr><td>105</td><td>165</td><td>very fine to fine</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>sand (silty)</td><td></td><td></td><td></td></tr> <tr><td>165</td><td>185</td><td>sandy gray clay</td><td></td><td></td><td></td></tr> <tr><td>185</td><td>200</td><td>very fine to coarse sand</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>and fine gravel with clay</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>lenses</td><td></td><td></td><td></td></tr> </tbody> </table>					FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2	topsoil				2	35	coarse sand and gravel				35	40	tan clay				40	60	fine to coarse sand and						fine to medium gravel				60	70	sandy tan clay				70	80	fine to coarse sand and						fine to medium gravel				80	105	tan clay				105	165	very fine to fine						sand (silty)				165	185	sandy gray clay				185	200	very fine to coarse sand						and fine gravel with clay						lenses			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																															
0	2	topsoil																																																																																																		
2	35	coarse sand and gravel																																																																																																		
35	40	tan clay																																																																																																		
40	60	fine to coarse sand and																																																																																																		
		fine to medium gravel																																																																																																		
60	70	sandy tan clay																																																																																																		
70	80	fine to coarse sand and																																																																																																		
		fine to medium gravel																																																																																																		
80	105	tan clay																																																																																																		
105	165	very fine to fine																																																																																																		
		sand (silty)																																																																																																		
165	185	sandy gray clay																																																																																																		
185	200	very fine to coarse sand																																																																																																		
		and fine gravel with clay																																																																																																		
		lenses																																																																																																		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/14/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/16/94 Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Jane Frederick</i>																																																																																																				