


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SE 1/4 Section Number 25 Township Number T 25 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 2 So 2 E 1/2 So Bentley KS.

2 WATER WELL OWNER: Jim Kehl
 RR#, St. Address, Box #: RR 3 Box 2 Valley Center KS 67147
 City, State, ZIP Code: Valley Center KS 67147
 Board of Agriculture, Division of Water Resources
 Application Number: 4-2585

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 4-2585
 Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.
 WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 4-2585
 Pump test data: Well water was 16 ft. after 20 hours pumping 40 gpm
 Est. Yield 40 gpm: Well water was 16 ft. after 20 hours pumping 40 gpm
 Bore Hole Diameter 11 in. to 48 ft. and 48 in. to 48 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 4-2585
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X
☐ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X
☐ 3 Fiberglass ☐ 12 Other (Specify below) Threaded X
 Blank casing diameter 5 in. to 12 ft., Dia 38 in. to 48 ft., Dia 12 in. to 48 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft., From 13 ft. to 48 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 48 ft., From 13 ft. to 48 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 48 ft., From 13 ft. to 48 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? West
 How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	14	clay			
14	30	sand			
30	31	clay			
31	48	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-25-85 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 4-28-85
 under the business name of Wannings Dullin by (signature) James Dullin
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

25

R

E

SEC.

25

NE

NE

NE

SE