


1 LOCATION OF WATER WELL: Sedgwick	FRACTION NEAR CENTER OF 1/4 1/4 NW 1/4	Section Number 25	Township Number T 25 S	Range Number R 2W E/W
Distance and direction from nearest town or city street address of well if located within city? 2 miles South, 1 1/4 mile East, 1/4 South of Bentley, Kansas				
2 WATER WELL OWNER: SEILER FARMS RR#, ST. ADDRESS, BOX #: Rt. 3 Box 69 CITY, STATE, ZIP CODE: Valley Center, Kansas 67147				
Board of Agriculture, Division of Water Resource Application Number: 27,599				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 177 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 17 FT. BELOW LAND SURFACE MEASURED ON 06/15/1994 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 900 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 177 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No		
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass Threaded Blank casing Diameter 16 in. to 85 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 19.750 lbs. / ft. Wall thickness or gauge No. .616 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 85 ft. to 122 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 137 ft. to 177 ft., From ft. to ft. from 20 ft. to 177 ft., From ft. to ft. from ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS				
0 2 topsoil				
2 5 sandy silt				
5 33 coarse sand and gravel				
33 40 blue clay				
40 55 fine to coarse sand and fine to medium gravel				
55 80 tan clay				
80 125 very fine to coarse sand				
125 135 tan clay				
135 177 very fine to coarse sand and fine gravel				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/15/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/18/94 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>				