

1 LOCATION OF WATER WELL: Fraction <u>NES 1/4 SW 1/4</u> Section Number <u>34</u> Township Number <u>T 25 S</u> Range Number <u>R 2 E</u>		County <u>Sedgewick</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>3 1/2 North Colwich KS.</u>			
2 WATER WELL OWNER: <u>Kenneth Knepp</u>		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #: <u>2001 ELPYCO</u>		Application Number: <u>38,801</u>	
City, State, ZIP Code: <u>WICHITA KS 67218</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NW NE SW SE S		4 DEPTH OF COMPLETED WELL: <u>23</u> ft. ELEVATION: <u>7-7-88</u> Depth(s) Groundwater Encountered 1. <u>9</u> ft. 2. <u>10</u> ft. 3. <u>100</u> ft. WELL'S STATIC WATER LEVEL <u>9</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>10</u> ft. after <u>1 1/2</u> hours pumping <u>200</u> gpm Est. Yield <u>200</u> gpm: Well water was <u>23</u> ft. after <u>1 1/2</u> hours pumping <u>200</u> gpm Bore Hole Diameter <u>14</u> in. to <u>23</u> ft., and <u>23</u> in. to <u>100</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>	
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter <u>8</u> in. to <u>13</u> ft., Dia. <u>13</u> in. to <u>160</u> PSI Casing height above land surface <u>12</u> in., weight <u>160</u> lbs./ft. Wall thickness or gauge No. <u>160</u> PSI		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>13</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft. GRAVEL PACK INTERVALS: From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>0</u> ft. to <u>9</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft., From <u>9</u> ft. to <u>23</u> ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>OPEN FIELD</u>	
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
0	2	Top ss. /	
2	6	clay	
6	23	SAND.	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-31-88</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>731888</u> This Water Well Record was completed on (mo/day/yr) <u>7-8-88</u> under the business name of <u>Weninger Dull</u> by (signature) <u>[Signature]</u>			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.			

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4