


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 36 Township Number: 25 Range Number: 2 E/W: W		Distance and direction from nearest town or city street address of well if located within city? 7 miles West of Valley Center, KS	
2 WATER WELL OWNER: Paul Seiler RR#, St. Address, Box #: Rt #3 Box 76 City, State, ZIP Code: Valley Center, KS 67147		Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION: 25 ft. below land surface measured on mo/day/yr 5/5/95 Depth(s) Groundwater Encountered 1 25 ft. 2 25 ft. 3 25 ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 5/5/95 Pump test data: Well water was 25 ft. after 11 hours pumping 180 gpm Est. Yield 25 gpm: Well water was 11 ft. after 180 hours pumping 180 gpm Bore Hole Diameter 11 in. to 180 ft. and 180 in. to 180 ft. WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☒ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☒	
5 TYPE OF BLANK CASING USED: ☒ Steel 3 RMP (SR) ☒ PVC 4 ABS Blank casing diameter 5 in. to 160 ft. Dia. 12 in. to 260 lbs./ft. Wall thickness or gauge No. 160 PSI Casing height above land surface 12 in. weight 260 lbs./ft. Wall thickness or gauge No. 160 PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 12 Other (specify) 7 Torch cut 180 SCREEN-PERFORATED INTERVALS: From 160 ft. to 180 ft. From 160 ft. to 180 ft. GRAVEL PACK INTERVALS: From 20 ft. to 180 ft. From 20 ft. to 180 ft.		CASING JOINTS: Glued ☒ Clamped ☒ Welded ☒ Threaded ☒	
6 GROUT MATERIAL: ☒ Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From 20 ft. to 180 ft. From 180 ft. to 180 ft. From 180 ft. to 180 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 50		FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 3 top soil			
3 74 sand			
74 120 clay			
120 132 white sand			
132 150 clay			
150 160 fine sand			
160 180 med. white sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/5/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5/11/95 under the business name of Neninger Drilling, Inc by (signature) Karina Morrissey			