

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Edwards</u>	<u>NW 1/4</u> <u>NW 1/4</u> <u>NE 1/4</u>	<u>16</u>	T <u>25</u> S	R <u>20</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

1/2 mile south, 2 miles east of Offerle

2 WATER WELL OWNER: <u>Earl o. Field</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>10405 Pineaire Drive</u>	Application Number:
City, State, ZIP Code: <u>Sun City, Arizona 85351</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>55</u> ft. ELEVATION:	Depth(s) Groundwater Encountered 1.....ft. 2.....ft. 3.....ft. WELL'S STATIC WATER LEVEL <u>10</u> ft. below land surface measured on mo/day/yr <u>12/12/90</u> Pump test data: Well water wasft. after hours pumping gpm Est. Yield <u>5</u> gpm: Well water wasft. after hours pumping gpm Bore Hole Diameter. <u>8 3/4</u> in. to <u>55</u> ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well <input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No. <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No		

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<input checked="" type="checkbox"/> 2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>4</u> in. to <u>45</u> ft., Dia.....in. to.....ft., Dia.....in. to.....ft.			
Casing height above land surface <u>18</u> in., weight.....lbs./ft. Wall thickness or gauge No. <u>SDR-26</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	<input checked="" type="checkbox"/> 8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From <u>45</u> ft. to <u>55</u> ft., From.....ft. to.....ft.			
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>55</u> ft., From.....ft. to.....ft.			

6 GROUT MATERIAL:			
1 Neat cement	2 Cement grout	<input checked="" type="checkbox"/> 3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From.....ft. to.....ft.			
What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
			14 Abandoned water well
			15 Oil well/Gas well
			16 Other (specify below)
			<u>Livestock</u>
Direction from well? <u>All</u>		How many feet? <u>5</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	<u>2</u>	<u>Top soil</u>			
2	50 <u>50</u>	<u>Tan clay</u>			
50	<u>55</u>	<u>Sand & tan clay</u>			
55		<u>Black clay</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/12/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224/ This Water Well Record was completed on (mo/day/yr) 12/31/90 under the business name of Carl Hayse Water Well Service by (signature) Carl Hayse

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4