			TER WELL REC	CORD Form W	WC-5 K		2a-1212 IC	No			
1 LOCATION			Fraction			ł	tion Numbe			Range Number	
County:	Edwar		SW 1/4		NE 1/4		35	т 2	.5 s	R 20 <b>g</b> w	
				t address of well if	located wit	hin ci	ty?				
L			of Offerle,	KS							
		NER: Bett	y Heinz								
RR#, St. Add City, State, Z		<pre>     * * * Pe     * Offe </pre>	te Heinz rle, KS 67	7563				Board of A Application	•	Division of Water Resource	
		CATION WITH	4 DEPTH OF	COMPLETED WEL	1 94		ft FLFV	ATION:			
AN "X" IN			Depth(s) Ground	dwater Encountere	d 1		<b>.</b> f	t. 2	ft. 3	<u>.</u> . , ft.	
<u> </u>	, N									7-10-02	
	; W	THE TEST TION TO THE WAR THE TEST TO THE CONTROL OF									
	! !	Bore Hole Diameter9in. to94ft., andin. toft.									
₩	!	E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
17 1	<u> </u>	-	1 Domestic	3 Feedlot	6 Oil field	wate	r supply	9 Dewatering	_ 12 (	Other (Specify below)	
	w  -	- SE	2 Irrigation	4 Industrial	7 Domesti	ic (law	n & garden)	10 Monitoring well	∺کنا	estock	
<u>                                     </u>		!		bacteriological samp	le submitted	to De				mo/day/yrs sample was sub	
ELTYPE OF	BI ANK C	ASING USED:	mitted	5 Wrought iron	9.0	oner	ete tile	er Well Disinfecte		No X ed X Clamped	
1 Steel	DLAINN C	ASING USED. 3 RMP (SI		6 Asbestos-Ceme			ete the (specify bel			ed	
2 PVC		4 ABS		7 Fiberglass			` '			eaded	
Plank assing	a diamata									in. to	
Blank Casing	y diamete		24 :		DR-26		I. W			.   U	
Casing height above land surface. 24 in., weight SDR-26 lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)											
1 Steel 2 Brass				5 Fiberglass 6 Concrete tile		9 AB					
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From94 ft. to											
From											
GI	RAVEL P.	ACK INTERVAL	LS: From	.Ÿラ ft. t	٥۲۷	)	ft., Fro	m	ft. t	to	
			From	ft. t	0		ft., Fro	m	ft. 1	to	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole .plug											
Grout Interv	/als: Fro	m20	ft. to Q.	ft., From .		ft.	to	ft., From .		ft. to	
I .			ble contamination					10 Livestock pens		Abandoned water well	
1 Septic tank 4 Lateral lines				7 Pit privy			11 Fuel storage		15 (	Dil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			12 Fertilizer storage			Other (specify below)		
3 Watertight sewer lines 6 Seepage pit			•	9 Feedyard				cticide storage		one	
Direction from well?  How many feet?											
FROM	TO		LITHOLOGIC LO	OG	FRO	MC	то		UGGING II	NTERVALS	
0	4	top soil			80		88	sand stone		1,2,17,120	
4	16	brown cl			8		88 1/2	ironated s		no	
16	19	sandy ta			88		92	sand stone		IIC .	
19	20		l gravel, c	00800	9:		95	gray shale			
20	26		lty clay	Oarse	<del></del>		75	gray share	·		
26	31										
	35	yellow s	<del></del>								
31			ne, dark								
35	47	fire cla									
47	50	gray sha		1 1 1							
50	55	sand stone, dark, with shale stre									
55	60	gray shale sand stone, hard									
60	64										
64	71	gray sha									
71	80			<u>one streaks</u>							
										nder my jurisdiction and was	
										nowledge and belief. Kansas	
Water Well C	ontractor	's Licence No	.134	This Wate	r Well Reco	ord wa	as completed	on (mo/day/yr) .	/18-	·U.	
under the bus	siness nai	me of Rosei	ncrantz-Ben	nis			by (:	signature)	π.	aleke	
								— ) L			