COUNTY: 024 EDWARDS ! NE	ion 1/4 NE 1/4 NE	1/4 ; ;	Section Nu 24	nber	Township N T <b>25</b>	lumber S	Range Number	r 
Distance and direction from nearest 2 S. 5 1/2 E. OF OFFERLE,KS	town or city street				·	<b>_</b>		
WATER WELL OWNER: MONTY HOS RR#, St. Address, Box # : RT.							ater Resource	
City, State, ZIP code : KINSLEY,	KS 67547-		Appl	ication N	ımber:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BGX:	; 4 DEPTH OF COMPL Depth(s) Groun	ETED WELL dwater Encou	<b>26</b> E	LEVATION:	0 12 ft. 2	2. <b>0</b> ft	. 3.	0 ft.
1 NW	WELL'S STATIC WA	TER LEVEL estdata: We	12 ft. be ll water w	low land s	surface meas ft. after	sured on mo O hours	/day/yr pumping	0 gpm
	Estimated Yield	O gpa: W	ell water	was O	ft. after	0 hours	pumping	0 gps
i W;;;; [	Bore Hole Diamet	er <b>8.</b>	75 in. to	<b>26</b> ft	, and	in. to	0 ft.	
· · · · · · · · · · · · · · · · · · ·	WELL WATER TO BE	USED AS: 01	DOMESTIC					
/	Was a chemical/b	acteriologic r sample was	al sample submitted	submitted	to departme	ent? <b>No ;</b> Water wel	l disinfected	? Yes
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in	CASIN to 21 ft., Dia	G JOINTS: <b>6L</b> in. t	UED 0 0 ft	., Dia	in. to	0 ft.		
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:	CASIN. to 21 ft., Dia 12 in., weight IAL: 07 PVC	G JOINTS: <b>6L</b> in. t	UED 0 0 ft	., Dia	in. to	0 ft.		
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT	G JOINTS: 6L in. t 0 lbs/f	UED o 0 ft t. Wall t 	., Dia hickness	in. to or gauge No 0 ft.	0 ft.		
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft.,	UED o 0 ft t. Wall t 	., Dia hickness ft. to ft. to	in. to or gauge No 0 ft. 0 ft.	0 ft.		
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  ft. to  ft. to  ft. to	in. to or gauge No 0 ft. 0 ft. 0 ft.	0 ft.		
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  ft. to  ft. to  ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. . 26	ow many feet?	6:
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possi Direction from well? SE  FROM : TO : O : 7 : TAN CLAY	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  oft. to ft. to ft. to ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. . 26	ow many feet?	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possi Direction from well? SE  FROM ; TO ;	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  oft. to ft. to ft. to ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. 0 ft.	ow many feet?	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possi Direction from well? SE  FROM   TO   0	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  oft. to ft. to ft. to ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. 0 ft.	ow many feet?	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possi Direction from well? SE  FROM ; TO ; 0 ; 7 ; TAN CLAY 7 ; 24 ; 05 SAND AND 17	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  oft. to ft. to ft. to ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. 0 ft.	ow many feet?	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possi Direction from well? SE  FROM ; TO ; 0 ; 7 ; TAN CLAY 7 ; 24 ; 05 SAND AND 17	CASIN to 21 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT  From 21 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	5 JOINTS: 6L in. t 0 lbs/f 26 ft., 0 ft., 0 ft.,	UED  O Oft  t. Wall t  From C  From C  From C  From C	., Dia hickness  oft. to ft. to ft. to ft. to	in. to or gauge No  O ft. O ft. O ft. O ft.	0 ft. 0 ft.	ow many feet?	

;/ CUNIKACION'S OK LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 3 /23/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224

This Water Well Record was completed on (mo/day/yr) 04/16/95 under the business name of CARL HAYSE WATER WELL SVC

by (signature)