

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Ford

Location listed as:

Section-Township-Range: 13-22-21WFraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): SE SE NE

Location changed to:

13-25-21WSE SE NEOther changes: Initial statements: initial township incorrect (22 S)Changed to: 25 S

Comments: _____

verification method: County maps, address and location provided,
mapping program on KGS websiteinitials: MS date: 3-3-06submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: FORD SE 1/4 SE 1/4 NE 1/4 13 T 22 S R 21 E

Distance and direction from nearest town or city street address of well if located within city?
 FROM OFFERLE - 1/2 MILES WEST AND 1 MILE SOUTH

2 WATER WELL OWNER: BURGHART, VANCE
 RR#, St. Address, Box #: 10273 136 ROAD Board of Agriculture, Division of Water Resources
 City, State, ZIP code: OFFERLE, KS 67563- Application Number:

3 LOCATE WELL'S LOCATION WITH
 AN "X" IN SECTION BOX:

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16

W

X

4 DEPTH OF COMPLETED WELL 85 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 12/22/05
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 35 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 10 in. to 85 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: DOMESTIC

Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CLAMPED
 Blank casing diameter 5 in. to 85 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 60 ft. to 80 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 85 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 32 TAN CLAY			
20	55	32 TAN CLAY			
55	78	10 FINE-MEDSAND 24 THINROCLAYER			
78	120	16 GRAY CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 12/22/05 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 12/23/05
 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Justin C. Cich*