LOCATION OF WATER WELL: Fracti COUNTY: FORD NE	on 1/4 NE 1/4 NE 1/4	24		T 25	\$!	R 22	Number W	
Distance and direction from nearest t SPEARVILLE - 4 MILES EAST ON HIGHWAY	-			·		'			
WATER WELL OWNER: AISTRUP, R RR#, St. Address, Box # : 12974 US H City, State, ZIP code : SPEARVILLE	EX IGHWAY 50 , KS 67876-	Boar Appl	d of Agri ication N	culture, i	Division	of Wat	er Res	ources	ł
LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX:					2.	0 ft.	3.	0	ft
NW	WELL'S STATIC WATER LEVEL Pump testdata: W								
N# NE	Estimated Yield 30 gpm:	Well water	was 0	ft. after	r 0 t	nours p	umping	0	g
¥ E	Bore Hole Diameter 1	0 in. to	228 ft	., and	in. t	:0	0 ft.	•	
SW SE	WELL WATER TO BE USED AS: D	OMESTIC							t I
	; Was a chemical/bacteriologi ; If yes, mo/day/yr sample wa	cal sample	submitted	to depart	tment? No Water	o; rwell	disinf	ected?	Y
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA	CASIN CASING JOINTS: C to 228 ft., Dia in. 2 in., weight 200 lbs/ L: PVC	to 0 ft	., Dia hickness	in. i	to 0	ft.			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE:	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/CL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft.,	to 0 ft /ft. Wall t , From 0 , From 0	hickness ft. to	or gauge O ft. O ft.	to 0 No. 17	ft.			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS:	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/CL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft.,	to 0 ft /ft. Wall t , From 0 , From 0 , From 0	hickness ft. to	or gauge O ft. O ft.	to 0 No. 17	ft.			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/CL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 0 ft., From 0 ft. to 0 ft., From 0 ft., From 0 ft. to 0 ft., From 0	to 0 ft.,	ft. to	0 ft. 0 ft. 0 ft. 0 ft.	No. 17	 t.	many	feet?	
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possibl Direction from well? NORTHEAST FROM : TO : L1	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/CL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., Company to 144 ft., From 30 ft. to 28 ft., From 144 ft. to 204 ft., From 30 ft. to 28 ft., From 30 ft. to 28 ft., From 144 ft. to 204 ft., From 25 ft., From 26 ft., From 30 ft. to 28 ft., From 27 ft., From 28 ft., From 29 ft., From 20	to 0 ft.,	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	 t.			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible continuous from well? NORTHEAST FROM TO LI O 20 01 TOPSOIL 05 CLA 20 40 39 SAND ROCK 35 C	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ L: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., Company to 1 ft., Thought and the contamination: ABANDONED With the contamination of the contamin	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to Mhat is the nearest source of possible Cirection from well? NORTHEAST FROM	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ EL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., SAW CUT CHOLOGIC LOG	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible Direction from well? NORTHEAST FROM	CASIN CASING JOINTS: Control to 228 ft., Dia in. 2 in., weight 200 lbs/ E: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., Grand Contamination: ABANDONED Williams ETHOLOGIC LOG EY 08 ROCK LAYERS CALACHIE 19 LAYERS TAN CLAY 02 FINE SAND. TAN CLAY 07 BLUE SHALE	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible Direction from well? NORTHEAST FROM 10 10 10 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05 CLA 20 40 30 SAND ROCK 32 TOPSOIL 05	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ L: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., Company to 1 ft., SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., SAW CUT AN GLAY 07 FT. SAND. CAN CLAY 07 BLUE SHALE CLAY CANDSTONE	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible Direction from well? NORTHEAST FROM TO 10 10 10 10 10 10 10 10 10 10 10 10 10	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ L: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., CTHOLOGIC LOG LY 08 ROCK LAYERS CALACHIE 19 LAYERS CALACHIE 19 LAYERS CAN CLAY 07 BLUE SHALE CLAY CLAY CLAY CLAY CASING JOINTS: CASING J	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible Direction from well? NORTHEAST FROM 1 TO 1 TOPSOIL 05 CLA 20 40 39 SAND ROCK 35 CLA 20 40 39 SAND ROCK 35 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 20 40 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 39 SAND ROCK 32 TOPSOIL 05 CLA 40 60 60 60 60 60 60 60 60 60 60 60 60 60	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ L: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., CTHOLOGIC LOG LY 08 ROCK LAYERS CALACHIE 19 LAYERS CALACHIE 19 LAYERS CAN CLAY 07 BLUE SHALE CLAY CLAY CLAY CLAY CASING JOINTS: CASING J	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			
TYPE OF BLANK CASING USED: CERTA LOC Blank casing diameter 5 in. Casing height above land surface 1 TYPE OF SCREEN OR PERFORATION MATERIA SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possible Direction from well? NORTHEAST FROM 10 10 10 10 10 10 10 10 10 10 10 10 10	CASIN CASING JOINTS: Company to 228 ft., Dia in. 2 in., weight 200 lbs/ EL: PVC SAW CUT From 144 ft. to 204 ft., From 0 ft. to 0 ft., From 30 ft. to 228 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., SAW CUT 30 ft., From 0 ft. to 1 ft., From 0 ft. to 1 ft., SAW CUT CHOLOGIC LOG SAY 08 ROCK LAYERS CALACHIE 19 LAYERS CALACHIE 19 LAYERS CAN CLAY 07 BLUE SHALE CLAY CANDSTONE CRAY CLAY CANDSTONE CRAY CLAY CANDSTONE	to 0 ft /ft. Wall t	hickness ft. to ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	No. 17	t. How			

under the business name of JOE'S WELL SERVICE, INC.

by (signature) Quairl curk

	_			٠.
-1	~	٠,	ler.	1 }

WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: | Fraction | Section Number COUNTY: FORD | NE 1/4 NE 1/4 NE 1/4 | 24 1 LOCATION OF WATER WELL: | Fraction Township Number Range Number ¦ T 25 S R 22 W 2 WATER WELL OWNER: AISTRUP, REX RR#, St. Address, Box # : 12974 US HIGHWAY 50 Board of Agriculture, Division of Water Resources City, State, ZIP code : SPEARVILLE, KS 67876-Application Number: LITHOLOGIC LOG 220 280 16 GRAY CLAY

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/14/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/18/08 under the business name of JOE'S WELL SERVICE, INC.