

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>	<u>NW 1/4 NW 1/4 NE 1/4</u>	<u>33</u>	T <u>25</u> S	R <u>24</u> E <u>(W)</u>

Distance and direction from nearest town or city street address of well if located within city?
From Wright, 3 miles north, 2 1/2 miles west, 1 north, and 3/8 west.

2 WATER WELL OWNER: Maurice Bleumer
 RR#, St. Address, Box # : 11550 Garnett Rd.
 City, State, ZIP Code : Dodge City, KS. 67801
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	5 ELEVATION:
	<u>320</u> ft.	<u>320</u> ft.
Depth(s) Groundwater Encountered <u>1</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>117</u> ft. below land surface measured on <u>4-12-05</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No		

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped	
2 PVC <u>(Circled)</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
			7 Fiberglass	Threaded	

Blank casing diameter 5 in. to 260 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SAR 17

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
			12 None used (open hole)	

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut <u>(Circled)</u>	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
			10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 260 ft. to 320 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 210 ft., From 220 ft. to 320 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite (Circled) 4 Other

Grout Intervals: From 4 ft. to 24 ft., From 210 ft. to 220 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>In pasture</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	4	Brown clay			
4	20	Yellow clay + sandrock			
20	35	White rock			
35	48	Yellow clay			
48	200	Shale + rock ledges			
200	220	Sticky gray clay			
220	285	Sandstone + clay layers			
285	300	Sticky gray clay			
300	320	Sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-12-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 533 This Water Well Record was completed on (mo/day/yr) 7-14-05 under the business name of Jantzen Water well Repair by (signature) [Signature]