

County: Ford Fraction: SE NE SW SE Sec. 36 T 25 S R 25 W

CORRECTION(S) TO WATER WELL COMPLETION RECORD Form WWC-5 (to rectify lacking or incorrect information)

Owner: Ron Bell

If location corrected, was listed as:

Location changed to:

Section-Township-Range: 36-25S-25W

36-25S-25W

Fraction (¼ calls): SE

SE NE SW SE

Other changes: Initial statements: Longitude: 100° 00.85' W. NAD27

Changed to: 100° 00.84' W NAD27

Comments: _____

Verification method: Well site address, Ford County online parcel search, latitude & longitude & KGS' "LEOWEB" conversion tool, and mapping tool & aerial photos on KGS website. Initials: DPA Date: 1/9/2019

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Avenue, Lawrence, KS 66047-3724
 Kansas Dept. of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.

Well ID

1 LOCATION OF WATER WELL:

County: Leavenworth Co.

Fraction $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$ SE $\frac{1}{4}$

Section Number 36

Township Number T25 S

Range Number R2 S E W


2 WELL OWNER: Last Name: Baer First: Ron

Business:
Address: 10879 106 Rd.
Address:
City: Dodge Co. Ky State: Ko. ZIP: 67801

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:

10595 Knottshaven Dr.

3 LOCATE WELL WITH "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: ...7.7... ft.

Depth(s) Groundwater Encountered: 1) ft.
 2) ft. 3) ft., or A) Dry Well
 WELL'S STATIC WATER LEVEL: ft.
 below land surface, measured on (mo-day-yr)
 above land surface, measured on (mo-day-yr) 9-1-78
 Pump test data: Well water was ft.
 after hours pumping gpm
 Well water was ft.
 after hours pumping gpm
 Estimated Yield: gpm
 Bore Hole Diameter: 1.0 in. to 7.7 ft. and
 in. to ft.

5 Latitude: 37°49.68'N (decimal degrees)

Longitude: 100°0.55'W (decimal degrees)
 Horizontal Datum: WGS 84 NAD 83 NAD 27
 Source for Latitude/Longitude:
 GPS (unit make/model: Garmin 120)
 (WAAS enabled? Yes No)
 Land Survey Topographic Map
 Online Mapper:

6 Elevation:10595...ft. Ground Level TOC

Source: Land Survey GPS Topographic Map
 Other

7 WELL WATER TO BE USED AS:

- | | | | | | | | | | | | | |
|---|---------------|------------|---------------|--|---|---|---|---|--|------------------------------|---------------------------------------|---|
| 1. Domestic:
<input type="checkbox"/> Household
<input checked="" type="checkbox"/> Lawn & Garden
<input type="checkbox"/> Livestock | 2. Irrigation | 3. Feedlot | 4. Industrial | 5. <input type="checkbox"/> Public Water Supply: well ID | 6. <input type="checkbox"/> Dewatering: how many wells? | 7. <input type="checkbox"/> Aquifer Recharge: well ID | 8. <input type="checkbox"/> Monitoring: well ID | 9. Environmental Remediation: well ID | 10. <input type="checkbox"/> Oil Field Water Supply: lease | 11. Test Hole: well ID | 12. Geothermal: how many bores? | 13. <input type="checkbox"/> Other (specify): |
|---|---------------|------------|---------------|--|---|---|---|---|--|------------------------------|---------------------------------------|---|

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter 5 in. to 7.7 ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface 1.6 in. Weight 200 lbs./ft. Wall thickness or gauge No. SOR 21

TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel Fiberglass PVC Other (Specify)
 Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)
 Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 6.0 ft. to 7.7 ft., From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 5.0 ft. to 7.7 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 4 ft. to 5.0 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination:
 Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage
 Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well
 Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well
 Other (Specify)

Direction from well? West Distance from well? 100 ft.

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	8	Soil Top			
8	35	Brown Sandy clay	70	73	mixed w/ little Rock
35	42	Brown clay	73	79	Rock & thin Sand
42	46	clay to med Sand			clay
46	48	Hard Rock			
48	57	clay to med Sand & gravel			
57	60	Hard Rock			
60	67	Brown Sandy clay			
67	70	clay to med Sand			

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 5/12/78 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 172 This Water Well Record was completed on (mo-day-year) 6-7-78 under the business name of Donagan Water Well Service Signature [Signature]

Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at <http://www.kdheks.gov/waterwell/index.html> KSA 82a-1212 **Revised 7/10/2015**