

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL:

County: Ford

Fraction NW 1/4 NE 1/4 SW 1/4 SE 1/4

Section Number 36

Township Number T 25 S

Range Number R 25 E 2 W


2 WELL OWNER: Last Name:

Business: Capital Deal
Address: 200 W. Beacon Rd.
City: Dodge City State: KS ZIP: 67801

First:

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: 10583 Brendon Lane

3 LOCATE WELL WITH 'X' IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 68 ft.

Depth(s) Groundwater Encountered: 1) 46 ft. 2) Dry Well

WELL'S STATIC WATER LEVEL: 46 ft.

below land surface, measured on (mo-day-yr) 10-13-16

above land surface, measured on (mo-day-yr)

Pump test data: Well water was after hours pumping gpm

Well water was after hours pumping gpm

Estimated Yield: gpm

Bore Hole Diameter: 1.0 in. to 68 ft. and

in. to ft.

5 Latitude: 37 49.73 N (decimal degrees)

Longitude: 100 06.94 W (decimal degrees)

Horizontal Datum: WGS 84 NAD 83 NAD 27

Source for Latitude/Longitude: N 37.828938 W 100.015789

GPS (unit make/model: WAAS enabled? Yes No)

Land Survey Topographic Map

Online Mapper:

6 Elevation: 2508 ft. Ground Level TOC

Source: Land Survey GPS Topographic Map

Other: KOLAP

7 WELL WATER TO BE USED AS:

- 1. Domestic: Household, Lawn & Garden, Livestock
2. Irrigation
3. Feedlot
4. Industrial
5. Public Water Supply: well ID
6. Dewatering: how many wells?
7. Aquifer Recharge: well ID
8. Monitoring: well ID
9. Environmental Remediation: well ID
10. Oil Field Water Supply: lease
11. Test Hole: well ID
12. Geothermal: how many bores?
13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No
Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded

Casing diameter: 5 in. to 6.8 ft. Diameter: in. to ft. Casing height above land surface: 15 in. Weight: 200 lbs./ft. Wall thickness or gauge No. 50R21

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)

SCREEN-PERFORATED INTERVALS: From 48 ft. to 68 ft. GRAVEL PACK INTERVALS: From 40 ft. to 68 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other

Grout Intervals: From 5 ft. to 40 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage

Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well
Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well

Direction from well? South Distance from well? 50 ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows describe soil layers from 0 to 68 ft depth.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 11-1-16 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 1730. This Water Well Record was completed on (mo-day-year) 12-1-16 under the business name of J. Pragan W. D. Well Services Signature: [Signature]