WATER WELL RECORD Form WWC-5			Division of Water				
Original Record		ge in Well Use		urces App. No.	m 1: 1: 1	Well ID	
1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4						□E 🗹 W	
2 WELL OWNER: L	ast Name: Musslin				ere well is located		
Business: Address: 11122 Che	otnut Dd		direction from n	earest town or int	ersection): If at owne	r's address, c	heck here: 🗹
Address: 11122 Che	Striut Ru						
City: Dodae Cit	ty State: KS	ZIP: 67801					
3 LOCATE WELL		MPLETED WELL: .	320 ↔	5 T	37.8844	86 ,	Constant Instant
WITH "X" IN	Denth(e) Groundwater	Encountered: 1) 14	949 It. 14 e	5 Latitude	-100.022	7.7(2428 /	decimal degrees)
	Depth(s) Groundwater Encountered: 1)						
NN	WELL'S STATIC WATER LEVEL:144						.110 27
		e, measured on (mo-day-	yr).11/19/2021		(unit make/model:)
NW NE		e, measured on (mo-day-			(WAAS enabled?		0)
		water was ft			l Survey 🔲 Topogr		
WE		rs pumping water was fi		☐ Onli	ne Mapper:		
SW SE		rs pumping					
	Estimated Yield:15	5 gnm			n :ft		
S	Bore Hole Diameter: .	9.5 in to 320			Land Survey		
1 mile		in. to	ft.	<u> </u>	Other		
7 WELL WATER TO							
1. Domestic: ✓ Household		ater Supply: well ID			ield Water Supply: le		
☐ Lawn & Garden		ng: how many wells? Recharge: well ID			11. Test Hole: well ID		
Livestock		ng: well ID			mal: how many bore		
2. Irrigation		tal Remediation: well ID			ed Loop 🔲 Horizon		
3. Feedlot	☐ Air Sparg		Extraction		Loop Surface D		
4. Industrial	☐ Recovery	☐ Injection		13.	r (specify):		
Was a chemical/bacter		nitted to KDHE? 🔲	Yes 🛮 No	If yes, date sa	ample was submitte	:d:	
Water well disinfected?							
8 TYPE OF CASING	USED: ☐ Steel ☑ PV	VC Dother	CASIN	IG JOINTS: [🗌 Glued 🗹 Clampe	d 🗌 Welded	. Threaded
Casing diameter 5 Casing height above land	in. to 520 ft.	., Diameter	in. to	ft., Diamete	erin. to	ft. ₹17	
TYPE OF SCREEN OF	SUFFACE	n. weight	10s./π.	wan tnickne	ss or gauge No	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
	nless Steel	PVC ₽VC		☐ Other	(Specify)		
_	vanized Steel		sed (open hole		(-p)		
SCREEN OR PERFOR	ATION OPENINGS A	ARE:	· -	,			
☐ Continuous Slot	☐ Mill Slot ☐ C	Sauze Wrapped 🔲 To			Other (Specify)		
Louvered Shutter	☐ Key Punched ☐ V	Wire Wrapped	w Cut 💹 N	one (Open Hole	e)		
SCREEN-PERFORATI	ED INTERVALS: From	m!99 ft. to .949	it., From		ft., From	tt. to	π.
GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 40 ft. to 320 ft., From ft. to ft. 9 GROUT MATERIAL: □ Neat cement □ Cement grout □ Bentonite □ Other Grout Intervals: From 5 ft. to 40 ft., From ft. to ft., From ft. to ft.							
Grout Intervals: From	5 ft. to 40	ft. From	ft to	ft From	ft to	fl.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Nearest source of possibl	le contamination: N	o potential source of con	tamination wit	hin 200 ft.		,,	
☐ Septic Tank	☐ Lateral Lin	es 🔲 Pit Privy		Livestock Pens	☐ Insecti	cide Storage	
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well							
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well							
☐ Other (Specify) Direction from well? West Distance from well? 60 ft.							
10 FROM TO	LITHOLO	OGIC LOG	FROM	TO L	ITHO. LOG (cont.) o	<u>.</u> r PLUGGING	GINTERVALS
							
Notes:							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo-day-year) 11/19/2021 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Con	ntractor's License No.	.846 This Wa	ater Well Rec	ord was comp	leted on (mo-day-y	/ear) .12/0.9	/2021
under the business nam	e of Mash Water We	II Service, LLC		<u> </u>		<u></u>	
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.							
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212							

Form	WWC5	
Contractor	Nash Water Well Service, LLC	
Well Owner	Matt Musslin	
Doc ID	1600923	

Lithology

Litrology		
	. 48	
0	6	TOP SOIL BROWN CLAY
6	18	WHITE ROCK CALICHE WHITE
		TAN CLAY WITH FINE SAND STREAKS
18	120	BLUE SHALE
120	150	BLUE CLAY
150	160	BLUE WITH GRAY CLAY WITH GRAY
		SANDSTONE 30%
160	180	GRAY CLAY WITH GRAY SANDSTONE
		MEDIUM TIGHT 30%
180	200	TIGHT GRAY SANDSTONE WITH GRAY
		CLAY MEDIUM TIGHT 70%
200	220	TIGHT GRAY SANDSTONE WITH GRAYCLAY MEDIUM TIGHT 50%
220	260	GRAY CLAY WITH GRAY SANDSTONE MEDIUM MEDIUM TIGHT 40%
260	280	MEDIUM GRAY SANDSTONE WITH GRAY CLAY MEDIUM 60%
280	300	GRAY SANDSTONE WITH GRAY CLAY MEDIUM 50%
300	320	GRAY SANDSTONE WITH GRAY CLAY MEDIUM 60%

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Matt Musslin
Doc ID	1600923

Lithology

320	340	GRAY RED CLAY WITH STREAKS OF GRAY SANDSTONE MEDIUM ?????30%
340	360	GRAY RED CLAY WITH STREAKS OF GRAY SANDSTONE TIGHT 20%
360	400	GRAY RED CLAY WITH STREAKS OF GRAY SANDSTONE TIGHT 15%