

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Ford Fraction SE 1/4 SE 1/4 NE 1/4 SE 1/4 Section Number 32 Township Number T 25 S Range Number R 26 E W

2 WELL OWNER: Last Name: Yeager First: Joey Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: [X]

3 LOCATE WELL WITH 'X' IN SECTION BOX: [Diagram] 4 DEPTH OF COMPLETED WELL: 240 ft. 5 Latitude: 37.831130 Longitude: 100.191758 6 Elevation: 2652 ft. [X] Ground Level [] TOC

7 WELL WATER TO BE USED AS: 1. Domestic [X] Household [] Lawn & Garden [] Livestock [] Irrigation [] Feedlot [] Industrial [] Public Water Supply [] Dewatering [] Aquifer Recharge [] Monitoring [] Environmental Remediation [] Air Sparge [] Soil Vapor Extraction [] Recovery [] Injection [] Oil Field Water Supply [] Test Hole [] Cased [] Uncased [] Geotechnical [] Geothermal [] Closed Loop [] Horizontal [] Vertical [] Open Loop [] Surface Discharge [] Inj. of Water [] Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? [] Yes [X] No If yes, date sample was submitted: Water well disinfected? [X] Yes [] No

8 TYPE OF CASING USED: [] Steel [X] PVC [] Other CASING JOINTS: [] Glued [X] Clamped [] Welded [] Threaded Casing diameter 6 in. to 240 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in. Weight lbs./ft. Wall thickness or gauge No. SDR17 TYPE OF SCREEN OR PERFORATION MATERIAL: [] Steel [] Stainless Steel [X] PVC [] Other (Specify) [] Brass [] Galvanized Steel [] None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: [] Continuous Slot [] Mill Slot [] Gauze Wrapped [] Torch Cut [] Drilled Holes [] Other (Specify) [] Louvered Shutter [] Key Punched [] Wire Wrapped [X] Saw Cut [] None (Open Hole) SCREEN-PERFORATED INTERVALS: From 180 ft. to 240 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 40 ft. to 240 ft., From ft. to ft.

9 GROUT MATERIAL: [] Neat cement [] Cement grout [X] Bentonite [] Other Grout intervals: From 5 ft. to 40 ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: No potential source of contamination within 200 ft. [] Septic Tank [] Lateral Lines [] Pit Privy [] Livestock Pens [] Insecticide Storage [] Sewer Lines [] Cess Pool [] Sewage Lagoon [] Fuel Storage [] Abandoned Water Well [] Watertight Sewer Lines [] Seepage Pit [] Feedyard [] Fertilizer Storage [] Oil Well/Gas Well [X] Other (Specify) Fish Pond Direction from well? South Distance from well? 500 ft.

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [] reconstructed, or [] plugged under my jurisdiction and was completed on (mo-day-year) 05/06/2020 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 05/08/2020 under the business name of Nash Water Well Service, LLC

Ford

32-T25-2611

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Joey Yeager
Doc ID	1515293

Lithology

0	20	TOP SOIL BROWN CLAY
20	30	TAN BROWN CLAY WITH FINE SAND STREAKS
30	40	TAN CLAY WITH ROCK & CALICHE
40	70	TAN CLAY WITH FINE SAND STREAKS
70	80	FINE COARSE SAND
80	100	TIGHT FINE MEDIUM SAND
100	120	FINE COARSE SAND
120	140	FINE COARSE SAND WITH TAN CLAY STREAKS
140	160	TAN CLAY WITH FINE SAND
160	180	FINE COARSE SAND TIGHT, SOME LOOSE LAYERS
180	200	FINE COARSE SAND LOOSE
200	205	TAN CLAY FINE SAND STREAKS
205	234	FINE COARSE SAND LOOSE
234	240	BLUE SHALE