WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION COUNTY:	OF WATER 035 GRAY		: NE	E 1,	4 SE														
Distance APPROX.	and direc 4 MILE EAS	tion fro T & 1/2	m neard NORTH (est tov Of Chai	in or		treet	address	of we	ll if I	ocate	d with	in city	?					
WATER WEL	LL OWNER: Address, ate, ZIP c	Rav # ·	IRSIK PO ROV	6 & B	MITC	: 1				Boa Apr			culture, imber: 1		ion of	Water	r Res	ources	
City, State, ZIP code : INGALLS, K LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				; ;	4 DE De	PTH OF	COMPLE	ETED WEL	L 27	8			0 0 ft.	2.	0	ft.	3.	0	f
۱ ۱	1	!	: :		WELL	'S STAT F		TER LEVE estdata:											/9 g
i	NYX	ì	i	-, ,	Esti	mated Y	ield	0 gp	m: Wel	l water	was	0	ft. aft	er	0 hou	rs pu	nping	. 0	9
			 	-! E !	Bore	Hole ()iamete	er		in. 1	0	0 ft	., and	iı	1. to	0	ft.		
;	S#	1				. WATER	WAS: (D2 RR16	ATION										ŀ
/	1	1	} }		₩as If y											ell di	isinf	ected?	١ ١
Casing ho TYPE OF S SCREEN OF	sing diame eight abov SCREEN OR R PERFORAT	ter e land s PERFORAT ION OPEN	urface ION MA IINGS AI	in. to -48 TERIAL RE:	in., : 01 : 03	278 ft., STEEL MILL SI	veight .OT	37 l	bs/ft.	0 f Wall	thick	ness		No:					
Casing he TYPE OF S SCREEN OF SCREEN PI	sing diame eight aboy SCREEN OR	ter e land s Perforat Ion open Interval	16 Surface TON MA TINGS AI	in. to -48 TERIAL RE:	in., : 01 03 From	278 ft., STEEL MILL SI 143 f	veight OT It to It to	i	bs/ft. t., fr t., fr	O 1 Wall Om Om	thick Oft.	to to	or gauge Oft. Oft.	. No		• •			
Casing here of the control of the co	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., fr t., fr t., fr t., fr	Oft.	thick 0 ft. 0 ft. 0 ft.	to to to to	or gauge Oft. Oft. Oft.	No:) ft.	How ma			
Casing horype of the Creen of Green place of Green	sing diame eight aboy SCREEN OR R PERFORAT ERFORATED AVEL PACK TERIAL tervals: the neares	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f 0 f 0 f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., fr t., fr t., fr t., fr	O Wall	thick 0 ft. 0 ft. 0 ft.	to to to to	or gauge oft. oft. oft.	Noi	oft.	How ma			
Casing heavy PE OF SCREEN OF SCREEN PE GRANGE FOR THE GRANGE FOR T	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., Fr t., Fr t., Fr t., Fr t., Fr	Wall Wall Om Om FROM 0 4	0 ft. 0 ft. 0 ft. 0 ft.	to to to to TO 4	or gauge Oft. Oft. Oft.	Noi	oft.	How ma			
Casing here of the control of the co	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., Fr t., Fr t., Fr t., Fr t., Fr	Oft. Wali Wali Om Om Oft. FROM 0 4 18 140	thick 0 ft. 0 ft. 0 ft, Fr	to to to to to TO 4 18 140 278	or gauge oft. oft. oft. oft. cemen	NO:) ft. J66ING	How ma			
Casing he TYPE OF: SCREEN OF SCREEN PR GROUT MA GROUT IN What is Direction	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., Fr t., Fr t., Fr t., Fr t., Fr	Wali Wali Om Om Om FROM 0 4 18	thick 0 ft. 0 ft. 0 ft, Fr	to to to to to to 4 18 140 278 0 0	or gauge oft. oft. oft. sackficemen	NO:) ft. J66ING	How ma			
Casing he TYPE OF: SCREEN OF SCREEN PR GROUT MA GROUT IN What is Direction	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., Fr t., Fr t., Fr t., Fr t., Fr	O	thick 0 ft. 0 ft. 0 ft, Fr	to to to to TO 4 18 140 278 0	or gauge oft. oft. oft. statement	NO:) ft. J66ING	How ma			
Casing he TYPE OF: SCREEN OF SCREEN PR GROUT MA GROUT IN What is Direction	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL O2 CEMEN From t source 1?	16 SUFFACE TION MA LINGS AI S: S: LT GROUT 4 ft.	in. to	in., 101 03 From From From Cont	278 ft., STEEL WILL SI 143 f O f O f	veight OT ft. to ft. to ft. to ft. to ft. to	278 f 0 f 0 f	t., Fr t., Fr t., Fr t., Fr t., Fr	O	thick O ft. O ft. O ft.	to to to to to 4 18 140 278 0 0 0	or gauge oft. oft. oft. oft. the backs of the cement	NO:) ft. J66ING	How ma			
Casing here of the secretary per of the secretary p	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	ter e land s PERFORAT ION OPEN INTERVAL INTERVAL 02 CEMEN From t source 1?	16 surface ION MA IINGS AI S: S: 4 ft. of pos	in. to -48 TERIAL RE: T to ssible	in., in., in., in., in., in., in., in.,	STEEL MILL SI 143 1 0 1 0 1 ft., Fi	veight OT (t. to it. to it. to it. to	278 1 0 1 0 1 0 1 0 1 0 SE	t., Fr t., Fr t., Fr t., Fr to RVED	0 Wali	thick Oft. Oft. I	to t	or gauge oft. oft. oft. oft. the backfine cements of the ceme	PLIFILL SAND &) ft.	How ma			
Casing here of the contract of	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	TER	16 SURFACE TON MA IINGS AI S: S: A ft. Of pos	in. to -48 TERIAL RE: T to ssible LITI	in., in., in., in., in., in., in., in.,	PTR ft., STEEL MILL SI 143 1 0 1 0 1 ft., Fritaminati	veight OT (t. to it. to it. to it. to	278 1 0 1 0 1 0 ft. DNE OBSE	t., Fr t., Fr t., Fr to., Fr	Wali Wali om om om ft. FROM 0 4 18 140 0 0 0 0 0 0	thick Oft. Oft. oft. Fr	to t	or gauge oft. oft. oft. oft. the backfine cement in the cement in t	PLUT GROUND SAND &) ft. JGGING	How ma			
Casing heavy Pe OF SCREEN OF SCREEN OF SCREEN PI GROUT MARGOUT IN THAT IS SOUTHALT IN SOUT	sing diame eight aboy SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neares n from wel	Ter Ter land s PERFORAT TON OPEN INTERVAL INTERVAL O2 CEMEN From t source 1? NDOWNER? lay/year) tor's Li	16 SURFACE TON MA LINGS AI S: S: S: S CERT 06/24 cense	in. to -48 TERIAL RE:	in., in 01 03 From From From Cont 18 f	PROPERTY OF THIS PROPER	veight OT It. to it. to it. to it. to it. to it. to ion: NO	278 1 0 1 0 1 0 ft. DNE OBSE	t., Fr t., Fr t., Fr to RVED	Offwali Wali om om om FROM 0 4 18 140 0 0 0 0 0 ed underst of mard was	thick Oft. Oft. Oft. r my ny kno	to t	or gauge oft. oft. oft. ft. center character diction e and be	PLIFIELL SAND &	Oft. JGGING GRAVE Kansa	How ma	RVALS		