SOUNTY: ARE ABAD									
COUNTY: 035 GRAY	; NE 1/	4 NE 1/4 SW	1/4 :	02		T 25	S 	; R 29	¥
Distance and direction from PPROX. 6.5 MILES NORTH A			t address of	well if lo	ocated wit	nin city?			
WATER WELL OWNER: RR#, St. Address, Box # :				Boar	rd of Agri	culture, Di	vision of	Water Re	sources
City, State, ZIP code :	INGALLS, KS	67853-		Арр	lication N	ımber: 1607	7		
LOCATE WELL'S LOCATION WI AN "X" IN SECTION BOX:							2. 0 f	t. 3	. 0 1
\	i i	Pump	testdata: W	iell water i	was O	ft. after	0 hour	s pumpin	i g 0 (
NW	NE; ;	Estimated Yield	600 gpm:	Well water	was 0	ft. after	0 hour	s pumpin	ıg 0 ç
W	-;; <u> </u>	Rore Hole Diame	ter 2	24 in. to	o 295 ft	., and	in. to	0 ft.	
SW;	SF!	WELL WATER WAS:	02 IRRIGATI	ION					ţ
		Was a chemical/ If yes, mo/day/	bacteriologi yr sample wa	ical sample as submitte	submitted d	to departm	ent? No ; Water we	ell disir	ofected? '
Blank casing diameter Casing height above land	16 in. to surface -36	295 ft., Di in., weigh	a in.	to 0 f					
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE	16 in. to surface -36 ITION MATERIAL: NINGS ARE:	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT	a in. t 37 lbs/	to Of	thickness	or gauge No			
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE	16 in. to surface -36 ITION MATERIAL: NINGS ARE:	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT From 205 ft. t	a in. t 37 lbs/	to Off /ft. Wall From From	thickness oft. to ft. to	or gauge No O ft. O ft.			
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE	16 in. to surface -36 ITION MATERIAL: NINGS ARE:	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT from 205 ft. t from 0 ft. t	a in. t 37 lbs/	to Off. Wall From From From	thickness Oft. to Oft. to Oft. to	or gauge No O ft. O ft.			
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE SCREEN PERFORATED INTERVA GRAVEL PACK INTERVA GROUT MATERIAL 03 BENT Grout Intervals: From	16 in. to surface -36 iTION MATERIAL: iNINGS ARE:	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT From 205 ft. t from 0 ft. t from 0 ft. t	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to Off. Wall From From From From From From Oft.	Oft. to Oft. to Oft. to	or gauge No O ft. O ft. O ft.			
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE SCREEN PERFORATED INTERVA GRAVEL PACK INTERVA GROUT MATERIAL 03 BENT Grout Intervals: From What is the nearest source	16 in. to surface -36 ITION MATERIAL: NINGS ARE: ILS: F ILS: F ONITE Oft. to se of possible	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT From 205 ft. t from 0 ft. t from 0 ft. t	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to Off. Wall From From From From From From Oft.	Oft. to Oft. to Oft. to	or gauge No O ft. O ft. O ft. O ft.	0 ft.	low many	feet?
Slank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE SCREEN PERFORATED INTERVA GRAVEL PACK INTERVA GROUT MATERIAL 03 BENT Grout Intervals: From What is the nearest source	16 in. to surface -36 ITION MATERIAL: NINGS ARE: ILS: F ILS: F IONITE Oft. to te of possible L AREA	295 ft., Di in., weigh 01 STEEL 01 CONT. SLOT From 205 ft. t from 0 ft. t from 0 ft. t	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to	Oft. to Oft. to Oft. to Oft. to Oft. to TO 13	O ft. O ft. O ft. O ft. O ft. TOPSOIL	0 ft.	low many	
Blank casing diameter Casing height above land FYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE SCREEN PERFORATED INTERVA GRAVEL PACK INTERVA GROUT MATERIAL 03 BENT Grout Intervals: From Hhat is the nearest sourc Direction from well? LOCA	16 in. to surface -36 ITION MATERIAL: NINGS ARE: ILS: F ILS: F IONITE Oft. to te of possible L AREA	295 ft., Di in., weigh 101 STEEL 101 CONT. SLOT from 205 ft. t from 0 ft. t from 0 ft. t from 0 ft. t 20 ft., From contamination:	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to Off /ft. Wall / , From , From , From , From , From , 13 165	thickness 0 ft. to 0 ft. to 0 ft. to 0 ft. to 10 ft. to 13 145 293	or gauge No O ft. O ft. O ft. O ft. CEMENT 6 CLAY CHLORINA	O ft. PLUGGING	low many	
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFORA SCREEN OR PERFORATION OPE SCREEN PERFORATED INTERVA GRAVEL PACK INTERVA GROUT MATERIAL 03 BENT Grout Intervals: From What is the nearest sourc Direction from well? LOCA	16 in. to surface -36 ITION MATERIAL: NINGS ARE: ILS: F ILS: F IONITE Oft. to te of possible L AREA	295 ft., Di in., weigh 101 STEEL 101 CONT. SLOT from 205 ft. t from 0 ft. t from 0 ft. t from 0 ft. t 20 ft., From contamination:	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to O f /ft. Wall , From , From , From O ft. ELL FROM 0 13 13 165	thickness 0 ft. to 0 ft. to 0 ft. to 0 ft. to 10 ft. to 13 13 165 293 0 0	O ft. O ft. O ft. O ft. O ft. CEMENT G CLAY CHLORINA	O ft. PLUGGING	low many	
GROUT MATERIAL O3 BENT Grout Intervals: From What is the nearest sourc Direction from well? LOCA	16 in. to surface -36 ITION MATERIAL: NINGS ARE: ILS: F ILS: F IONITE Oft. to te of possible L AREA	295 ft., Di in., weigh 101 STEEL 101 CONT. SLOT from 205 ft. t from 0 ft. t from 0 ft. t from 0 ft. t 20 ft., From contamination:	a in. t 37 lbs/ c 295 ft., c 0 ft., c 0 ft., c 0 ft., c 0 ft.,	to Off. Wall From From From From From From From 10 13 13 165 0	thickness 0 ft. to 0 ft. to 0 ft. to 0 ft. to 3 to 13 to 165 to 293 to 0 to 0 to 0 to	O ft. O ft. O ft. O ft. CEMENT S CLAY CHLORINA	O ft. PLUGGING	low many	

completed on (mo/day/year) 10/18/91 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 145
Under the business name of HENKLE DRILLING & SUPPLY
Under the business name of HENKLE DRILLING & SUPPLY

Water Well Record was completed on (mo/day/yr) 02/01/92

Under the business name of HENKLE DRILLING & SUPPLY

Daught R. Henkle