


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Gray		SW 1/4 SE 1/4 NE 1/4	20	T 25S S	R 29W EW
Distance and direction from nearest town or city street address of well if located within city? 2 1/2 miles E of Charleston, KS--					
2 WATER WELL OWNER: Cheyenne Drilling		#1 Strawn Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: Box 916		Application Number: 920193			
City, State, ZIP Code: Garden City, KS 67846					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 106 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 106 ft. below land surface measured on mo/day/yr 05-19-92 Pump test data: Well water was 120 ft. after 1 hours pumping 110 gpm Est. Yield 110 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 220 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 220 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. .032					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 160 ft. to 220 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 120 ft. to 220 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug					
Grout Intervals: From 1 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? Southeast		How many feet? 180			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	30	Caliche			
30	73	Sand			
73	77	Clay			
77	121	Sand and streaks of Clay			
121	150	Sandy Clay			
150	163	Clay			
163	206	Sand			
206	220	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05-19-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430. This Water Well Record was completed on (mo/day/yr) 05-19-92 under the business name of Howard Drlg. Co. Box 806 Beaver, OK 73938 (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					