


1 LOCATION OF WATER WELL:		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 28	Township Number T 25 S	Range Number R 29 SW		
Distance and direction from nearest town or city street address of well if located within city? From Ingalls, Kansas across river bridge follow river road for 1/2 miles West							
2 WATER WELL OWNER:		Glasco Drilling Co. (Irvin)		Rig #6			
RR#, St. Address, Box #:		P. O. Box 1499		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:		Great Bend, Kansas 67530		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:							
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 5-12-81							
Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield 75 gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter 8 in. to 60 ft. and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:							
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped			
<u>2 PVC</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded			
Blank casing diameter 5 in. to 60 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface 12 in., weight 200 psi lbs./ft. Wall thickness or gauge No. 1/2 21							
6 TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement			
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	9 ABS	12 None used (open hole)			
2 Louvered shutter	4 Key punched	6 Wire wrapped	7 Saw cut	13 Drilled holes			
SCREEN-PERFORATED INTERVALS: From 15 ft. to 55 ft. From ft. to ft.							
From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 15 ft. to 60 ft. From ft. to ft.							
From ft. to ft. From ft. to ft.							
7 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 15 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination: None							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
How many feet?							
Direction from well?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	15	Top soil & medium to coarse sand					
15	30	Coarse sand					
30	60	Coarse sand & sand rock layers					
8 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 13, 1981 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) March 11, 1982 under the business name of Joe's Well Service, Inc. Cimarron, KS by (signature) Tom Crisick							
INSTRUCTIONS: Use typewriter or ball-point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							