

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>		FRACTION: <u>NE 1/4 NE 1/4 SE 1/4</u>		SECTION NUMBER: <u>17</u>		TOWNSHIP NUMBER: <u>T 25 S</u>		RANGE NUMBER: <u>R-3 E/W</u>	
2 WATER WELL OWNER: <u>City of Mt. Hope</u>									
RR#, St. Address, Box # : <u>1201 N OHIO</u>				Board of Agriculture, Division of Water Resources					
City, State, ZIP Code : <u>35</u>				Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>35</u> ft. ELEVATION:							
		Depth(s) Groundwater Encountered: 1 <u>15</u> ft. 2 <u>35</u> ft. 3 <u>10-20-04</u> ft. WELL'S STATIC WATER LEVEL: <u>15</u> ft. below land surface measured on mo/day/yr. Pump test data: Well water was <u>100</u> gpm: Well water was <u>100</u> ft. after <u>100</u> hours pumping <u>100</u> gpm. Est. Yield <u>100</u> gpm: Well water was <u>100</u> ft. after <u>100</u> hours pumping <u>100</u> gpm. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u> </u> ; If yes, mo/day/yr sample was submitted <u>Yes</u> No <u> </u>									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u> </u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u> </u> Blank casing diameter <u>8</u> in. to <u>25</u> ft. Dia <u>2.40</u> in. to <u>160 p.s.i.</u> lbs./ft. Wall thickness or guage No. <u>160 p.s.i.</u>									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) <u> </u> 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) <u> </u> 7 Torch cut									
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>35</u> ft. From <u> </u> ft. to <u> </u> ft. GRAVEL PACK INTERVALS: From <u>15</u> ft. to <u>35</u> ft. From <u> </u> ft. to <u> </u> ft.									
6 GROUT MATERIAL: 1 Neat cement 3 Bentonite 4 Other <u> </u> Grout Intervals: From <u>3</u> ft. to <u>15</u> ft. From <u> </u> ft. to <u> </u> ft.									
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u> </u> Direction from well? <u>South East</u> How many feet? <u>12 feet</u>									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
<u>0 3 Top Soil</u>									
<u>3 15 Clay</u>									
<u>15 35 Med Sand</u>									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-20-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>11-03-04</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>E. J. [Signature]</u>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									