

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: Sedgewick		NW 1/4 NE 1/4 SW 1/4	15		T 25 S		R 3 EW	
Distance and direction from nearest town or city street address of well if located within city? 2.25 m. east of Mt. Hope								
2 WATER WELL OWNER:		JR Tucker						
RR#, St. Address, Box # :		25901 W. Hwy K96						
City, State, ZIP Code :		Mt. Hope KS						
Board of Agriculture, Division of Water Resources Application Number:								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:						
		Depth(s) Groundwater Encountered 1. 22 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18.8 ft. below land surface measured on mo/day/yr 4/24/98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . in. to . ft., and . in. to . ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:								
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded								
Blank casing diameter 2 in. to 15 ft., Dia in. to . ft., Dia in. to . ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 2 Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From ft. to . ft. From ft. to . ft., From ft. to . ft. GRAVEL PACK INTERVALS: From 14 ft. to 25 ft., From ft. to . ft. From ft. to . ft., From ft. to . ft.								
6 GROUT MATERIAL:								
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 2 ft., From 2 ft. to 14 ft., From ft. to . ft. What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage former USG								
Direction from well? How many feet?								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
5 7 Clay, ab. silt, gray brn								
10 12 Silt, clay, brn								
15 17 Silt, clay, brn								
20 22 Silt, clay, trace fine sand, brn								
Flushing water by R. Taylor								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/22/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 4/1/98 under the business name of T.E.S.T. by signature Bob Robinson by LL								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								