

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SEDGWICK	SW 1/4 SW 1/4 SW 1/4	22	T 25 S	R 3 E (W)

Distance and direction from nearest town or city street address of well if located within city?

1 Mile East, 1 Mile South of MT. HOPE

26320 W 93 N

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
RICK DE JESUS	26320 W. 93rd N.	MT. HOPE, KS 67108	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	30 ft.	
	Depth(s) Groundwater Encountered	ft. 1. ft. 2. ft. 3.
	WELL'S STATIC WATER LEVEL	30 ft. below land surface measured on mo/day/yr 10/26/93
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield gpm: Well water was	ft. after hours pumping gpm
	Bore Hole Diameter	in. to ft. and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic WAS 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes X No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued.....Clamped.....
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded.....
Blank casing diameter 1 1/4 in. to ft., Dia			Threaded.....
Casing height above land surface 3 FT. below in., weight			lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) NA
SCREEN-PERFORATED INTERVALS:	From NA ft. to NA ft., From		
	From ft. to ft., From		
GRAVEL PACK INTERVALS:	From ft. to ft., From		
	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS:	From 3 ft. to 1 ft., From			
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? NORTH				How many feet? 60 FT.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			25	3	SAND & Gravel 4.32 FT.
			3	2	Neat Cement 0.29 FT.
			4		REMOVED 1 1/4 STEEL PIPE
			15		SAND
			3		CEMENT, MUSHROOM AT TOP
			1		Soil

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/26/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 10/26/93 This Water Well Record was completed on (mo/day/yr) 10/26/93 under the business name of Rick De Jesus by (signature) Rick De Jesus
