

LOCATION OF WATER WELL: Fraction center of Section Number 28 Township Number T 25 S Range Number R 3 E
 County: Sedgwick

Distance and direction from nearest town or city street address of well if located within city?

1 3/4 S. Mt. Hope


WATER WELL OWNER: Elliot Bros.
 RR#, St. Address, Box #: Mt. Hope, Ks. 67108
 City, State, ZIP Code: Mt. Hope, Ks. 67108

Board of Agriculture, Division of Water Resources

Application Number: 19682

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL 92 ft. ELEVATION: 1350



Depth(s) Groundwater Encountered 1. 25 ft. 2. 28 ft. 3. 800 ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 8/15/81

Pump test data: Well water was 28 ft. after 1 hours pumping 800 gpm

Est. Yield 1000 gpm: Well water was 28 ft. after 1 hours pumping 800 gpm

Bore Hole Diameter 30 in. to 92 ft. and 92 in. to 92 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)
 2 PVC 4 ABS

5 Wrought iron 6 Asbestos-Cement
 7 Fiberglass

8 Concrete tile 9 Other (specify below)

CASING JOINTS: Glued Clamped X
 Welded
 Threaded

Blank casing diameter 16 in. to 54 ft. Dia. 54 in. to 54 ft. Dia. 54 in. to 54 ft.

Casing height above land surface 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 3/4"

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel
 2 Brass 4 Galvanized steel

5 Fiberglass 8 RMP (SR)
 6 Concrete tile 9 ABS

10 Asbestos-cement
 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
 2 Louvered shutter 4 Key punched

5 Gauzed wrapped
 6 Wire wrapped
 7 Torch cut

8 Saw cut 11 None (open hole)
 9 Drilled holes
 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 54 ft. to 92 ft. From 54 ft. to 92 ft. From 54 ft. to 92 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 92 ft. From 10 ft. to 92 ft. From 10 ft. to 92 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines
 2 Sewer lines 5 Cess pool
 3 Watertight sewer lines 6 Seepage pit

7 Pit privy 8 Sewage lagoon
 9 Feedyard

10 Livestock pens 14 Abandoned water well
 11 Fuel storage 15 Oil well/Gas well
 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage None

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	8	Fine Sand			
8	12	Clay			
12	20	Fine Sand / Clay			
20	25	Clay			
25	35	Med. Sand			
35	40	Clay			
40	55	Med. Sand			
55	58	Clay			
58	92	Med Sand - small gravel			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/15/81 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 238 This Water Well Record was completed on (mo/day/yr) 6/10/82

under the business name of Weninger Irrigation by (signature) Kathleen Weninger

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

28

R

3

E

SEC.

28

4/50 1/4

1/4

1/4