

1 LOCATION OF WATER WELL:

Fraction

X C-SW 1/4

SE 1/4

Section Number

Township Number

Range Number

County: Gray

15

T

25S

S

R 30 E/W

Distance and direction from nearest town or city street address of well if located within city? From Garden City go East to Gray Coun.

line then 4mi East North to location.

2 WATER WELL OWNER: J. E Mooney Anddarko Production

RR#, St. Address, Box #


Ingalls, Kansas 67853

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

Application Number: T 82-51

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL... 200 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL... 60 ft. below land surface measured on mo/day/yr 2/6/82

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield .60 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter... 9 in. to 200 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted

Water Well Disinfect? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)

2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued..... Clamped.....

Welded.....

Threaded.....

Blank casing diameter 5 in. to 100 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 28 in., weight 2.78 lbs./ft. Wall thickness or gauge No. 256

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel

2 Brass 4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 PVC

8 RMP (SR)

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot

2 Louvered shutter 4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 100 ft. to 200 ft. From ft. to ft. From ft. to ft.

From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 200 ft. From ft. to ft. From ft. to ft.

From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines

2 Sewer lines 5 Cess pool

3 Watertight sewer lines 6 Seepage pit

7 Pit privy

8 Sewage lagoon

9 Feedyard

11 Fuel storage

12 Fertilizer storage

13 Insecticide storage

15 Oil well/Gas well

16 Other (specify below)

Direction from well? Northeast of water well

How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 2 surface

2 10 clay

10 35 gravel

35 62 fine sand

62 78 sandy clay

78 138 medium to large sand

138 162 sandy clay

162 195 medium to large sand

195 200 black shell

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) February 6, 1982 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) February 25, 1982

under the business name of Carlile Water Well Service Inc. by (signature) Edward E. Shears

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.