


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

9
T R EW sec 1/4 1/4 1/4 No.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas State Dept. of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Gray	Township name Logan	Fraction Mid. of SW 1/4	Section number 25	Town number TS 25	Range number RW 30
Distance and direction from nearest town or city: 1 mile south of Charleston, Ks. Street address of well location if in city:			3 Owner of well: Don Renick Address: Ingalls, Ks.			
Locate with "X" in section below: 			Sketch map:		4 Well depth: 174 ft. Date of completion 1-24-75 Well diameter 26 in.	
					5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
					6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well	
					7 Casing: Material St. Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. Weight 34.2 lbs./ft. 1 in. to ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No in. to ft. depth	
2	Type and color of material		From	To	8 Screen: Manufacturer Johnson Division Type Galv. Dia. 16" Slot/gauze 100 Length 20' Set between 150 ft. and 170 ft. Pens: 30-150, 170-174 Gravel pack <input type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 14" down	
	Fine to med. sand & clay		0	5		
	Med. to coarse gravel		5	36		
	Fine to med. sand & gravel (Loose)		36	68		
	Fine to med sand & gravel 15% clay (Loose)		68	92		
	Brown clay		92	136		
	Fine to med. sand & gravel 10% clay		136	153		
	Fines: Fine to med. sand & gravel (Loose)		153	170		
	Brown, gray, & yellow clay (tight)		170	174		
	Shale (Hard)		174	180		
					9 Static water level: 11 ft. below land surface Date 1-29-75	
					10 Pumping level below land surfaces: 22 ft. after 3 hrs. pumping 1236 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1200 g.p.m.	
					11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
					12 Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade	
					13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Clay Puddled Depth: From 0 ft. to 10 ft.	
					14 Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
					15 Pump: <input type="checkbox"/> Not installed Manufacturer's name FMC-Peerless Model number 3787 HP Volts Length of drop pipe 120 ft. capacity 800 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
					17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilg. Co. 208 Business name Box 493 Garden City, Ks. Address License No. Signed Date 3-14-75 Authorized representative	
(use a second sheet if needed)						
16 Remarks: elevation	Electric motor. (We did not sell, so don't know volts or horsepower) Good Well. No possible contamination.					
Topography:	<input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley					

Forward the white, blue and pink copies to the Kansas State Dept. of Health.

Form WWC-5