


LOCATION OF WATER WELL:		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 27	Township Number T 25 S	Range Number R 30 SW
County: Gray		Distance and direction from nearest town or city street address of well if located within city? From Charleston, Kansas - 2 miles South and 2 1/2 miles West			
2 WATER WELL OWNER: Wertman Ranch, Inc.		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code : Ingalls, Kansas 67853					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL..... 155 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1..... ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 10-29-82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 155 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes..... No..... XXX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXX No XXX			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued XXX Clamped..... Welded..... Threaded.....	
Blank casing diameter 8 in. to 155 ft., Dia..... in. to ft., Dia..... in. to ft.					
Casing height above land surface 12 in., weight 200 psi		lbs./ft. Wall thickness or gauge No. SDR 21			
6 TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 2 Brass 4 Galvanized steel	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify)..... 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify).....	11 None (open hole)	
7 SCREEN-PERFORATED INTERVALS: From 130 ft. to 150 ft., From ft. to ft.					
8 GRAVEL PACK INTERVALS: From 18 ft. to 155 ft., From ft. to ft.					
9 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 5 ft. to 18 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well? Northwest		How many feet? 150 ft.			
10 LITHOLOGIC LOG		11 LITHOLOGIC LOG			
FROM	TO	0 150' Sandy topsoil & fine sand	FROM	TO	11 LITHOLOGIC LOG
35		45' Medium sand			
45		60' Medium sand & brown clay layers (sandy)			
60		90' Medium sand & sandrock layers			
90		120' Medium to coarse sand			
120		150' Medium to coarse sand & clay layers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Oct. 30, 1982 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) June 23, 1983
under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) Lenny Crick

INSTRUCTIONS: Use typewriter or ball point pen, **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to **WATER WELL OWNER** and retain one for your records.