


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

| | | | | | |
|--|--|---|--|----------------------------------|-----------------------------|
| 1. Location of well: | County GRAY | Fraction NW 1/4 SE 1/4 NW 1/4 | Section number 30 | Township number T 25 S | Range number R 30 |
| 2. Distance and direction from nearest town or city: <i>South of Piercerville</i> | 3. Owner of well: R.R. or street: City, state, zip code: | | Dale Corley 612 Center Garden City, KS 67846 | | |
| 4. Locate with "X" in section below:  | Sketch map: | | 6. Bore hole dia. 26 in. Completion date 12-20-76 Well depth 225 ft. | | |
| 5. Type and color of material | From | To | 7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary | | |
| | | | 8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other | | |
| | | | 9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP 36.0 ft./in. Weight 36.0 lbs./ft. Dia. 16 in. to 226 ft. depth Wall Thickness: inches or Dia. 16 in. to 226 ft. depth Gage No. | | |
| | | | 10. Screen: Manufacturer's name Johnson Screen Type G 1v. Dia. 16" Slot/gauze 3 Length 10' Set between 150-150 ft. and 210-220 ft. Perf: 80-150 ft. and 160-210, 220-225 ft. Gravel pack? yes Size range of material 1" 2" | | |
| | | | 11. Static water level: 31 ft. below land surface Date 11-5-76 | | |
| | | | 12. Pumping level below land surfaces: 64 ft. after 3 hrs. pumping 1500 g.p.m. 64 ft. after 3 hrs. pumping 1500 g.p.m. Estimated maximum yield 1500 g.p.m. | | |
| | | | 13. Water sample submitted: no mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date | | |
| | | | 14. Well head completion: Pitless adapter 12 inches above grade | | |
| | | | 15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft. | | |
| | | | 16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type Field WNC Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | |
| | | | 17. Pump: Not installed Manufacturer's name Goulds U.S. Pumps Model number 12 JMO HP 1/2 Volts 115 Length of drop pipe 140 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other | | |
| 18. Elevation: | (Use a second sheet if needed) | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business name <i>Minter Wilson Drilling</i> License No. Address <i>1000 10th St.</i> Date <i>2-24-77</i> Signature <i>Minter Wilson</i> Authorized representative | | |
| Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley | 19. Remarks: We did not install the motor | | | | |

The
Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

CORLEY GIGOT
FINNEY COUNTY
10-12-76

Location: NW 30-25-30 30 Ft. west of pivot
Static Water Level- 40'

Test #3 Pivot 10

| | | |
|-----|-----|---|
| 0 | 1 | Top soil |
| 1 | 6 | Fine sand |
| 6 | 41 | Med. coarse gravel |
| 41 | 45 | Fine to med. sand and gravel clay trace tight |
| 45 | 61 | Fine to med. sand and gravel |
| 61 | 71 | Brown sandy clay |
| 71 | 77 | Fine to med. sand and gravel |
| 77 | 82 | Brown sandy clay |
| 82 | 96 | Med. sand to med. coarse gravel Loose |
| 96 | 121 | Fine to med. sand and gravel Loose |
| 121 | 130 | Brown sandy clay |
| 130 | 147 | Brownish yellow clay stick |
| 147 | 159 | Fine to med. sand and gravel Loose |
| 159 | 202 | Brown sandy clay |
| 202 | 215 | Fine to med. sand some yellow rock small clay Stks. |
| 215 | 222 | Med. coarse gravel mixed yellow white rock Loose |
| 222 | 225 | Yellow clay and shale |

T.D. 225

80' Plain
70' Perf
10' Screen
50' Perf
10' Screen
5' Perf