WATER WELL RECORD	Form WWC-5		r Resources; App. No. ∟		
1 LOCATION OF WATER WELL:	Fraction	Section Number	1 *		
County: Finney	NW 1/4 NE 1/4 SE 1/4	32	T 25 S		
Distance and direction from nearest town or city street address of well if located within city? South side of Garden City, 9 miles S., Latitude:					
located within city? South side of Garden City, 9 miles S., Latitude: 1-1/3rds miles E., 2,550 Ft. N. & 940 Ft. W. Longitude:					
2 WATER WELL OWNER: Martin G.	The state of the s	Longitude:	·		
	arallel Road	Elevation:			
	ty, KS 67846	Datum:			
Data Conection Method.					
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL					
LOCATION WITH AN "X" IN Depth(s) Groundwater Encountered (1)					
SECTION BOX: WELL'S STATIC WATER LEVEL164ft. below land surface measured on mo/day/yr10-26-06					
Est. Yieldgpm: Well water wasft. after hours pumpinggpm					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
W E Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
(2) Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
SW SE SE					
Was a chemical/bacteriological sample submitted to Department? Yes					
Sample was submitted					
S					
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Weld					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded XX					
Casing height above land surface					
TYPE_OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)					
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot (3)Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: From					
From It. to It., From It. to It.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage (14 Abandoned water well below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? northeast How many feet? 50 ft. north & 80 ft. east					
FROM TO LITHOLOGIC	LOG FROM	M TO	PLUGGING INT	EKVALS	
See attached log					
bee accaence 10g					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged					
under my jurisdiction and was completed on (mo/day/year) .10-26-06 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 10-27-06					
under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Aug Killer					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone					
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at					
http://www.kdhe.state.ks.us/geo/waterwells.					

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 276-8269 P.O. Box A • **GARDEN CITY, KANSAS 67846**

Martin Nusser Finney County 10-2-06

Location: SE $\frac{1}{6}$ 32-25-32 - Harry Lightner Corner on Hwy. 83 - $1\frac{1}{6}$ miles east, mile north. & mile west to well - offset - 40 ft. south & 80 ft. west

Static Water Level - 150 ft.

Test #2

0' to 1' - Top soil 1' to 18' - Brown sandy clay 18' to 21' - Brown clay 21' to 36' - Fine to medium sand & gravel 36' to 84' - Fine to medium sand & gravel with some coarse 84' to 110' - Fine to medium sand & gravel with clay streaks 110' to 156' - Brown sandy clay 156' to 179' - Brown clay 179' to 208' - Fine to medium sand & fine gravel 208' to 234' - Brown sandy clay 234' to 247' - Fine to medium sand - small clay streaks 247' to 284' - Brown sandy clay 284' to 291' - Fine to medium sand & fine gravel 291' to 325' - Brown sandy clay 325' to 358' - Fine to medium sand 358' to 379' - Brown clay 379' to 390' - Fine sand 390' to 404' - Brown sandy clay 404' to 410' - Fine sand & fine gravel 410' to 454' - Brown clay with gravel streaks 454' to 498' - Brown sandy clay - tight 498' to 500' - Fine to medium sand & gravel 500' to 508' - Brown clay with brown rock-40% 508' to 526' - Brown yellow clay - hard 526' to 530' - Shale - hard