WATER WELL RECORD	Form WWC	`-5 Di	vision of Wate	r Resources App. No	12,226
1 LOCATION OF WATER WELL			on Number	Township No.	Range Number
County: FINNEY	1/4 NW 1/4 SE 1/4	SE 1/4	26	T 25 S	R 32 □E 🗹 W
Street/Rural Address of Well Locati	on; if unknown, distance & dir	ection Globa	l Positioning	g System (GPS) in	formation:
from nearest town or intersection: If at owner's address, check here .		e 🗌. 🛛 Latitu	Latitude: (in decimal degrees)		
GARDEN CITY-7 M S ON HWY 83 TO ANNIE SCHEER ROAD,			Longitude: (in decimal degrees)		
4-1/4 M E, 1 M S, 1310 FT N & 1225 FT W		Eleva	Elevation: <u>Datum</u> : WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: STERLING SMITH TRUST		Datum Colleg	Collection Method:		
RR#, Street Address, Box #: 368 W. 5TH ST.			GPS unit (Make/Model:)		
	SSELL, KS 67665		Digital Map/Ph	ioto, 🔲 Topographi	c Map, 🗌 Land Survey
		<u>Est. A</u>	ccuracy: <	3 m, 🗌 3-5 m, 🗍	5-15 m, 📋 >15 m
3 LOCATE WELL	OF COMPLETED WELL	370	ft		
WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL					
N WELL'S STATIC WATER LEVEL 148					ay/yr3-17-11
Pump test data: Well water wasft. after hours pumping					ping gpm
EST. YIELI	Dgpm. Well water wa	sft	. after	hours pum	ping gpm
w E Bore Hole I	Diameter 30 in. to 370				
	TER TO BE USED AS: D P	ublic water suppl	ly ∐ Ge	othermal [] [njection well
SW SE Domest	ic 🗌 Feedlot 🗌 Oil : n 🗌 Industrial 🗌 Dom				
X Mas a chem	ical/bacteriological sample sub	mitted to Depart	$tment? \square$	Ves V I No	
S If yes	mo/day/yr sample was submit	ted			
	disinfected? 🗌 Yes 🔽 No				
		r			
CASING JOINTS: Glued					
Casing diameter			ft., D	Diameter	. in. to ft.
Casing height above land surface	12 in., Weight 42	2.05lbs./f	t., Wall thi	ckness or gauge N	o
TYPE OF SCREEN OR PERFORAT		_			
Steel Stainless Steel		Other (Specify)		
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Louvered shutter Key punched 🔽 Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: From 20 ft. to					
6 GROUT MATERIAL: 🗌 Neat	coment Coment grout	Bentonite [\Box Other	<u></u>	
Grout Intervals: From	ft to 20 ft From	ft to	ft	From	. ft. to
Grout Intervals: From0					
	ral lines 🗌 Pit privy 🛛 🗌 I	ivestock pens	Insecticide		er (specify below)
Sewer lines Cess		uel storage	Abandone		
Watertight sewer lines Seer Direction from well WEST	age pit [] reedyard [] r	ertilizer storage Distance from w	Oil well/g	as well	
		ROM TO		OG (cont.) or PLU	GGING INTERVALS
			DITTIO. D		
SEE ATTACHED I	.OG				
7 CONTRACTORIS OR LANDOW	NED'S CEDTIEICATION.	This water wall -	Was 17 const		usted or nursed
7 CONTRACTOR'S OR LANDOW	ted on (molday/year) 3-17-11	and this r	was VI consti record is true	to the best of my^{1}	nowledge and belief
under my jurisdiction and was completed on (mo/day/year) .3-17-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)3-22-11					
under the business name of MINTER	R-WILSON DRILLING CO.,	NC by (s	signature) 🛒	ora Keller	1
INSTRUCTIONS: Use typewriter or ball poi	nt pen. PLEASE PRESS FIRMLY and	PRINT clearly. Ple	ease fill in blank	s and check the correc	t answers. Send three copies
(white, blue, pink) to Kansas Department of H Telephone 785-296-5522. Send one copy to	iealth and Environment, Bureau of W WATER WELL OWNER and retain	ater, Geology Secti	on, 1000 SW Ja rds. Include fe	ackson St., Suite 420, we of \$5.00 for each c	1 opeka, Kansas 66612-1367. constructed well. Visit us at
http://www.kdheks.gov/waterwell/index.html.	with the set of the and to an				ton visit as at

The Professionals MINTER-WILSON DRILLING CO. United and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME	JIM STALEY
COUNTY	FINNEY
DATE	2-11-11

LOCATION: SE 1/4 26-25-32 - HWY. 83 & ANNIE SCHEER ROAD - 4-1/4 MILES EAST, 3/4 OF A MILE SOUTH & 1/4 MILE WEST - 60 FT. EAST OF EXISTING WELL

STATIC WATER LEVEL - 155 FT.

TEST #1

0' TO 1' - TOP SOIL 1' TO 26' - BROWN CLAY 26' TO 40' - FINE TO MEDIUM SAND & GRAVEL 40' TO 147' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE 147' TO 160' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE - 10% CLAY - TIGHT 160' TO 187' - BROWN CLAY 187' TO 205' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY 205' TO 220' - BROWN CLAY WITH GRAVEL STREAKS 220' TO 252' - BROWN CLAY 252' TO 263' - BROWN CLAY WITH WHITE ROCK MIXED 263' TO 309' - FINE TO MEDIUM SAND & FINE GRAVEL 309' TO 328' - FINE TO MEDIUM SAND & GRAVEL WITH CLAY STRIPS 328' TO 338' - BROWN CLAY 338' TO 356' - FINE TO MEDIUM SAND & FINE GRAVEL - 10% CLAY 356' TO 362' - BROWN CLAY 362' TO 370' - BROWN YELLOW CLAY

370' TO 395' - SHALE - HARD PULL DOWN