WATËR WELL REC	CORD	Form WW	C- 5	Division o	of Water Resource	s Ann No	15,581
1 LOCATION OF WA	TER WELL:	Fraction		Section Nun		ip Number	
County: Finney		SE 1/4 NW 1/4		30	T 25	S	R 33 HW
	from nearest town or cit				ioning Systems	(decimal de	grees, min. of 4 digits)
Parallel RD, 2 M.	1comb-4 M. S., 1			Latitude:			
2 WATER WELL OW				Longitude:			
RR#, St. Address, Box		-	•	Elevation:			
City, State, ZIP Code		ity, KS 67846		Datum: _			
3 LOCATE WELL'S	4 DEPTH OF COME	• -			ction Method:		
LOCATION LOCATION	4 DEI III OF COM	LETED WELL		.7.4.2	16.		
WITH AN "X" IN SECTION BOX: N NW	Est. Yieldgpm WELL WATER TO B. 1 Domestic 3 Feed	TER LEVEL: : Well water was. : Well water was. E USED AS: 5 Pu dlot 6 Oil fie	blic water s	below land sft. afterft. after supply pply	hours hours hours Air conditioni Dewatering	d on mo/day s pumping. s pumping. ng 11 In 12 O	gpm gpm jection well ther (Specify below)
SW SE	2) Irrigation 4 Ind Was a chemical/bacter Sample was submitted	iological sample sul	bmitted to I	Department?	Yes N	ю. Ж ;	
5 TYPE OF CASING U	SED: 5 Wrought I	ron 8 Co	ncrete tile	<u>C</u>	ASING IOINTS	: Glued	Clamped
1)Steel 3 RMF	(SR) 6 Asbestos-	Cement 9 Oth	er (specify	below)	AISH (G JOH (I E		XX
2 PVC 4 ABS	7 Fiberglass						d
Blank casing diameter	16 in. to 300	ft., Diameter	i	n. to	ft., Diameter		. in. toft.
Casing height above land	surface12	in., Weight	2.05	bs./ft. Wa	all thickness or	guage No.	
TYPE OF SCREEN OR P			0.4	DC	11 04-	(C:6.)	
	nless Steel 5 Fiber, vanized Steal 6 Conc	glass 7 PVC		.BS Asbestos-Cen		r (Specify) used (oper	n hala)
SCREEN OR PERFORA) 10 A	Asoesios-Cell	ilelit 12 Nolle	used (open	ii iioie)
	(3)Mill slot 5 G		Torch cut	9 Drilled	holes 11 N	one (open)	hole)
2 Louvered shutter	4 Key punched 6 W	ire wrapped 8	Saw cut	10 Other (s	specify)		
SCREEN-PERFORATED	INTERVALS: From	400 ft. to	465	ft., Fr	om	ft. to .	ft.
	From	ft. to		ft., Fr	om	ft. to .	ft.
GRAVEL PACK	INTERVALS: From						
	From	ft. to		ft., Fr	om	ft. to .	ft.
6 GROUT MATERIAL	· 1 Neat cement /2	Cement grout 3 F	Rentonite	4 Other			
Grout Intervals: From	n 0 ft. to	25 ft From		ft. to	ft From		ft. toft.
What is the nearest source					,		
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livesto		13 Insecticide s		16 Other (specify
2 Sewer lines		8 Sewage lagoon	11 Fuel st		14 Abandoned		below)
3 Watertight sewer	lines 6 Seepage pit	9 Feedyard	12 Fertiliz	er storage	15 Oil well/gas	well	•
Direction from well?							
FROM TO	LITHOLOGIC	LOG	FROM	TO	PLUG	GING INT	ERVALS
	See attached 1c	g					
7 CONTRACTORS OF	I ANDOMNEDIC CE	DTIELCATION	Th:				4-1 (2) 1 1
7 CONTRACTOR'S OR under my jurisdiction and	LANDOWNER'S CE was completed on (mo/	day/year) 2-27	This water 7-09 and	well was (1) this record is	constructed, (2) true to the best	of my kno	ted, or (3) plugged wledge and belief
Kansas Water Well Contra							
under the business name o	f Minter-Wilson I	rlg.,Co., Inc	by	(signature)	norarke	lev	
INSTRUCTIONS: Use typewi	riter or ball point pen. PLEA	SE PRESS FIRMLY and	PRINT clear	ly. Please fill in	n blanks, underline	or circle the o	correct answers. Send to
three copies to Kansas Departme 785-296-5522. Send one t	ent of Health and Environment o WATER WELL OWN						
http://www.kdheks.gov/waterwe		IIIII OIIO		100		- Jones woll	

The Professionals MINTER-WILSON DRILLING CO. | Irrigation and Domestic Water Systems Complete Installation

and Repairing

INCORPORATED

P.O. Box A • **GARDEN CITY, KANSAS 67846** Phone 620-276-8269

NAME

REEVE CATTLE COMPANY - CIRCLE #49

COUNTY

FINNEY

DATE

1-17-09

LOCATION:

NE 1/4 30-25-33 - FROM PARALLEL & ANNIE SHEER ROAD -

1-3/4 MILES NORTH & 1/4 MILE WEST

- WEST OF PIVOT

STATIC WATER LEVEL - 240 FT.

TEST #1

0' TO 3' - TOP SOIL

3' TO 21' - FINE SAND

21' TO 47' - BROWN CLAY WITH LAYERS OF BROWN SANDY CLAY

47' TO 139' - FINE & MEDIUM SAND & GRAVEL

139' TO 145' - BROWN CLAY

145' TO 168' - FINE & MEDIUM SAND & GRAVEL

168' TO 188' - BROWN CLAY WITH STREAKS OF SAND & GRAVEL

188' TO 201' - FINE & MEDIUM SAND & GRAVEL

201' TO 321' - FINE & MEDIUM SAND & GRAVEL WITH STRIPS OF **BROWN SANDY CLAY**

321' TO 322' - CEMENTED GRAVEL - HARD PULL

322' TO 328' - BROWN CLAY WITH LAYERS OF SAND & GRAVEL

328' TO 422' - FINE TO MEDIUM SAND & GRAVEL WITH STREAKS OF **BROWN CLAY**

422' TO 428' - BROWN CLAY

428' TO 456' - BROWN CLAY WITH LAYERS OF SAND & GRAVEL 50%

456' TO 494' - HARD BROWN CLAY, YELLOW & GRAY CLAY & **BROWN ROCK 20%**

494' TO 500' - SHALE - 400 LB. PULL DOWN