WATER WELL RECORD	Form WWC-5	Division of Water R	esources App. No	20,055	
1 LOCATION OF WATER WELL:	Fraction			Range Number	
County: FINNEY	1/4 NW 1/4 NW 1/4 SW	1		R 33 □E 🗹 W	
Street/Rural Address of Well Locatio					
from nearest town or intersection: If at owner's address, check here			Latitude: (in decimal degrees)		
· —			Longitude: (in decimal degrees)		
GARDEN CITY-8 M S TO PETE SMITHS RD, 3-2/3RDS M W,		Elevation:			
2,260 FT. NORTH & 4,903 FT. W		Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: LEE AND BRENDA REEVE		Collection Method:			
RR#, Street Address, Box #: PO BOX 1036			GPS unit (Make/Model:)		
City, State, ZIP Code : GARDEN CITY, KS 67846			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
OAN.		Est. Accuracy:			
3 LOCATE WELL					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 395 ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
SECTION BOX: N Depth(s) Groundwater Encountered (1)					
Pump test data: Well water wasft. after hours pumping gpm					
EST. YIELDgpm. Well water wasft. after					
W Bore Hole Diameter .30					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
Demostic Deposition Deficiency					
SW SE Domestic					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ☐ Yes ✓ No					
5 TYPE OF CASING USED: S	eel PVC Other				
CASING JOINTS: Glued Clamped W Welded Threaded					
Casing diameter					
Casing height above land surface1	2 in Weight 42.05	lbs /ft Wall thickr	ness or gauge No	.250	
			less of gauge ivo	, .	
TYPE OF SCREEN OR PERFORATION MATERIAL: □ Other (Specify) □ Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN_PERFORATED INTERVAL	S: From 295 ft to 3	95 ft From	ft t	fr	
SCREEN-PERFORATED INTERVALS: From					
CDANEL DACK INTEDIAL	S: From 20 ft to 2	15 & Erom 2	75	395	
GRAVEL FACK INTERVAL	From ft. to				
COOUT MATERIAL. Nest es	ment 51 Coment grout DR	tonita	It. U	0 IL.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From0 ft. to20 ft., From215 ft. to275 ft., From ft. to ft.					
What is the nearest source of possible co		. –			
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)					
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedvard ☐ Fertilizer storage ☐ Oil well/gas well N/A					
Direction from well					
FROM TO LITHOLO	OGIC LOG FROM	TO LITHO. LOG	i (cont.) <u>or</u> PLU	GGING INTERVALS	
	:				
SEE ATTACHED LO	OG I				
		 			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed	l on (mo/day/year) 9-10-09	and this record is true to t	the best of my kr	nowledge and belief.	
Kansas Water Well Contractor's License					
under the business name of MINTER-WILSON DRLG. CO., INC. by (signature) Mara Heller					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					

Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

P.O. Box A • **GARDEN CITY, KANSAS 67846** Phone 620-276-8269

NAME

REEVE CATTLE COMPANY - CIRCLE #38

COUNTY

FINNEY

DATE

6-24-09

LOCATION:

SW 1/4 28-25-33 - FROM PARALLEL & ANNIE SCHEER ROAD -

2 MILES NORTH, 1-1/2 MILES EAST, 3/4 OF A MILE SOUTH & 1/4 MILE WEST - NORTHWEST EDGE OF CIRCLE

STATIC WATER LEVEL - 210 FT.

TEST #2

0' TO 1' - TOP SOIL

1' TO 14' - BROWN SANDY CLAY

14' TO 25' - BROWN CLAY

25' TO 42' - FINE SAND

42' TO 160' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

160' TO 170' - CEMENTED SAND & GRAVEL - COARSE

170' TO 202' - MEDIUM TO COARSE GRAVEL - TIGHT

202' TO 207' - BROWN BLUE CLAY

207' TO 226' - BLUE CLAY

226' TO 236' - BROWN CLAY

236' TO 252' - BROWN CLAY WITH GRAVEL STREAKS

252' TO 267' - BROWN CLAY

267' TO 282' - BROWN SANDY CLAY

282' TO 293' - BROWN CLAY WITH SMALL GRAVEL STREAKS

293' TO 327' - FINE TO MEDIUM SAND & GRAVEL

327' TO 347' - BROWN CLAY

347' TO 358' - FINE TO MEDIUM SAND & GRAVEL - CLAY STREAKS

358' TO 381' - FINE TO MEDIUM SAND & FINE GRAVEL

381' TO 396' - BROWN CLAY - STICKY

396' TO 432' - BROWN CLAY

432' TO 447' - BROWN SANDY CLAY

447' TO 457' - BROWN CLAY

457' TO 463' - BROWN YELLOW CLAY

463' TO 467' - YELLOW CLAY - HARD PULL DOWN

467' TO 470' - SHALE - HARD PULL DOWN